

**WPB 18 LTX BL 125 Quick (613075850) Cordless angle grinder**  
**18V; Cardboard box**

Order no. 613075850  
EAN 4007430286079



Product may differ from Image



- Unique encapsulated Metabo brushless motor with optimum protection from dust provides quick work progress and the highest efficiency
- Slim design for low-fatigue working
- Paddle switch with dead man function: safe to operate due to an ergonomically integrated switch
- Fast brake system for highest user safety stops the disc within a matter of seconds after switching off
- Metabo Quick for tool-free disc change by means of a quick-locking nut
- Tool-free adjustable guard; twist-proof
- Battery pack can be swivelled for better access in hard to reach places
- Electronic safety shutdown: reduces kickback if the disc stops unexpectedly - for high user safety
- Overload protection: protects the motor from overheating
- Electronic soft start for smooth start-up
- Restart protection: prevents unintentional start-up after battery pack change
- Detachable dust protection filter protects motor from coarse particles
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

## Technical data

### Characteristics

|                             |                  |
|-----------------------------|------------------|
| Type of battery pack        | Li-Power         |
| Battery voltage             | 18 V             |
| Disc-Ø                      | 125 mm / 5 "     |
| No-load speed               | 9000 rpm         |
| Spindle thread              | M 14             |
| Weight without battery pack | 1.8 kg / 4 lbs   |
| Weight with battery pack    | 2.6 kg / 5.7 lbs |

### Vibration

|                              |                      |
|------------------------------|----------------------|
| Surface grinding             | 5 m/s <sup>2</sup>   |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Grinding with sandpaper      | 2.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

### Noise emission

|                              |          |
|------------------------------|----------|
| Sound pressure level         | 82 dB(A) |
| Sound power level (LwA)      | 93 dB(A) |
| Uncertainty of measurement K | 3 dB(A)  |

## Scope of delivery

Guard  
Inner support flange  
Quick-locking nut  
Side handle  
Dust protection filter  
without battery pack, without charger