Datum: 07/05/2020



# **LABREPORT**: Determination of resistance to liquids

## (ISO 2812-4:2007) of oil+2C Gold with and without B-component

Library

1 Goal: Determine the influence of B-component on liquid resistance of Oil+2C Gold

## 2 Testpanel and method:

Wood specie	Oak		
Pre-treatment wood	Sanded: P120	Brushed: none	Others: none

Method	Method of application	Manually
	Method of drying	Oxidative
	Time between application oil and drops	7 days
	Completely cured	Yes

Method	Horizontal/ angel	Horizontal
	Substance A	Water
	Substance B	Coffee
	Substance C	Cola
	Substance D	Red Wine
	Duration of the test	24h

#### **Quotation**:

0: No marks 1: Slight visible mark 2: Visible mark 3: Damage of the wood

Datum: 07/05/2020

**LABREPORT**: Determination of resistance to liquids



### 3 Results:





MUYLLE FACON

Sanded P120	Oil+2C Gold Pure + B comp			Oil+2C Gold White + B comp		
	1h	4h	24h	1h	4h	24h
Water	0	0	0	0	0	0
Coffee	0	0	0	0	0	1
Cola	0	0	0	0	0	0
Red wine	0	0	0	0	0	1
Conclusion	Very good resistance			Good resistance. Some small stains of		
				coffee	and wine aft	er 24h





Sanded P120	Oil+2C Gold Slate Grey + B comp			Oil+2C Gold Charcoal + B comp		
	1h	4h	24h	1h	4h	24h
Water	0	0	0	0	0	0
Coffee	0	0	0	0	0	0
Cola	0	0	0	0	0	0
Red wine	0	0	0	0	0	0
Conclusion	Very good resistance			Very	good resista	ance





Sanded P120	Oil+2C Gold Pure WITHOUT B comp			Oil+2C Gold White WITHOUT B comp		
	1h	4h	24h	1h	4h	24h
Water	0	0	0	0	0	0
Coffee	0	0	1	0	0	2
Cola	0	0	0	0	0	0
Red wine	0	1	1	0	0	2
Conclusion	Some small stains of coffee after 24			Stains of co	offee and win	e after 24h
	h and wine after 4h and 24h					

Datum: 07/05/2020








				Miller .			
Sanded P120	Oil+2C Gol Slate Grey WITHOUT B comp			Oil+2C Gold Charcoal WITHOUT B			
				comp			
	1h	4h	24h	1h	4h	24h	
Water	0	0	0	0	0	0	
Coffee	0	0	1	0	0	1	
Cola	0	0	0	0	0	0	
Red wine	0	0	1	0	0	1	
Conclusion	Some small stains of coffee and		Some small stains of coffee and wine				
	w	wine after 24h			after 24h		


#### 4 Conclusion:

- Significant difference in resistance to liquids of oil+2C gold when using B-component.

We can illustrate this by making the total sum of the quotations after 24 hours (0: No marks 1: Slight visible mark 2: Visible mark 3: Damage of the wood).

Lower sum means better results.





Johan Boonaert 07/05/2020