Gas Industrial Ovens

General Features:

- Quality Construction for long life
- Stainless Steel Front Standard Stainless top & sides available (T430)
- Heavy duty steel deck with flanged sides (16A)
- 4-Cell "Power-Pak"
 Burner System for better distribution of heat and better baking ability
- Thermostat(s) 250° - 550° standard 300° - 650° optional
- Space Saver Only 50" wide
- Stackable
 Multiple options for flexibility
- Aluminized Interior Standard
- Easily Serviceable
 Most controls can be replaced from the front of the unit
- WarrantyOne year parts and labor
- PowerGas LP or NAT
- Specific Features
 of the CW41I listed on back





MORE FOR LESS

More Heating Space per Floor Space More Heating Capacity per Sales Dollar More Performance per Gas Dollar









 Floor space
 50" (127cm) wide x 42" (106.7cm) deep* x 52" (132.1cm) high

 Shelf size
 42" (105.7cm) wide x 32" (81.3cm) deep x 7" (17.8cm) high

 Shipping weight
 550 lbs (249.5kg)

 Capacity
 Two 18"x26" trays

 Gas
 Maximum 60,000 BTU input

 Opening required for installation: 22"
 * Handle adds 2.5"(6.4cm) to depth



Adjustable Legs

Durable Construction

The CW4II is built with *prime 20-gauge cold-rolled top and sides* with a 14-gauge base. The *interior is made of Armco Type 1,20-gauge aluminized steel*. The CW4II comes standard with stainless steel front, or optional all stainless steel finish. The stainless steel is made of high quality, 18-gauge 430 stainless; the door interior is 18 gauge stainless.

Energy Efficiency

The CW4II features our *new energy-saving "Power-Pak"* 4-cell burner system and our unique baffle system. These make our ovens highly efficient and eliminate hot spots. The heavily insulated walls, coupled with our special vent system, reduces heat loss and keep your gas dollars from going up the stack. The CW4II is powered by 60,000 highly efficient BTUs (each) which increases its efficiency and recovery rate.

Capacity

The CW41I deck size measures 42"x32"x7". The CW41I will hold two (2) 18"x26" trays. Heating time will vary according to product.

Space Saver

Because the controls are under the door, the CW41I requires *less installation space* than our competition. This enables you to free up valuable workspace. The actual width needed is a mere 50" for a 42"x32" deck, almost a foot less than the competition. The CW41I *can convert into a CW42I or CW43ISC by stacking*, either initially or after your business grows. This option gives you two or three 42"x32" decks in only 56" of space.

Design Plus

The CW4II has the controls in lower front for ease of operation and space savings. This also places the controls in their own air-conditioned area so they are not affected by outside influences. In addition, the CW4II is totally thermocoupled and allows you to replace individual parts as opposed to throwing away the whole system.

