



ROOFING NAILS

THE SPECIFICATION OF ROOFING NAILS

NAIL LENGTH	APPROX. NAILS PER LB	POINT	NAIL DIAMETER	HEAD DIAMETER	COATING *	STEEL
3/4" *	348	DIAMOND	.120" (11 GAUGE)	.437" (7/16")	ELECTRO GALV / HOT DIPPED GALV	C1004 - C1006
7/8" *	306	DIAMOND	.120" (11 GAUGE)	.437" (7/16")	ELECTRO GALV / HOT DIPPED GALV	C1004 - C1006
1" *	272	DIAMOND	.120" (11 GAUGE)	.437" (7/16")	ELECTRO GALV / HOT DIPPED GALV	C1004 - C1006
1-1/4" *	218	DIAMOND	.120" (11 GAUGE)	.437" (7/16")	ELECTRO GALV / HOT DIPPED GALV	C1004 - C1006
1-1/2" *	186	DIAMOND	.120" (11 GAUGE)	.437" (7/16")	ELECTRO GALV / HOT DIPPED GALV	C1004 - C1006
1-3/4" *	152	DIAMOND	.120" (11 GAUGE)	.437" (7/16")	ELECTRO GALV / HOT DIPPED GALV	C1004 - C1006
2"	144	DIAMOND	.120" (11 GAUGE)	.437" (7/16")	ELECTRO GALV / HOT DIPPED GALV	C1004 - C1006
2-1/2"	114	DIAMOND	.120" (11 GAUGE)	.437" (7/16")	ELECTRO GALV / HOT DIPPED GALV	C1004 - C1006
3"	92	DIAMOND	.120" (11 GAUGE)	.437" (7/16")	ELECTRO GALV / HOT DIPPED GALV	C1004 - C1006



* MEET ASTM F1667-05 SPECIFICATIONS
HOT DIPPED GALVANIZATION CONFORMS TO ASTM A 153, CLASS D SPECIFICATIONS

PRIME SOURCE
BUILDING PRODUCTS, INC.

800-676-7777
www.primesourcebp.com
www.grip-rite.com