

JOBSITE SERIES

6' BAKER SAFECLIMB

- Anti-Slip Rungs
- Climb through platform
- Anti-Slip Deck
- 1,100 lb load capacity
- Stackable up to 3 units high for 24' reach
- Quick and easy height adjustment
- Meets ANSI, CSA and OSHA

METALTECH®



**NO TOOLS
REQUIRED**

**OSHA
ANSI
CSA**

MEETS

12'

REACH

1,250 lb

LOAD CAPACITY

**BUILT TOUGH FOR
SAFETY**

JOBSITE SERIES
6' BAKER
SAFECLIMB

SAFECLIMB




ANTI-SLIP DECK
Made of 1/2" anti-slip film coated plywood




ANTI-SLIP RUNGS
Nonslip rungs help with moisture issues on footwear.



DOUBLE LOCKING 5" CASTERS



CLIMB THROUGH PLATFORM
Keeps your weight in the center of the unit for safer climbing.



STACKABLE UP TO 18'*
Easily stackable up to three units high in order to reach a range of 24'.



QUICK AND EASY HEIGHT ADJUSTMENT
Platform height adjusts at 2" increments from 27" to 73". Double prong spring-loaded locking mechanism.

6' BAKER, SAFECLIMB	
ASSEMBLED DIMENSIONS (WDXH)	74.75 X 29.75 X 75 IN. (189.9 X 75.6 X 190.5 CM)
PACKAGE DIMENSIONS (WDXH)	75 X 30.5 X 5.25 IN. (190.5 X 76.2 X 13.3 CM)
WEIGHT	120.3 LB (54.7 KG)
LOAD CAPACITY	1,250 LB (567 KG), COMBINED WEIGHT OF USER + MATERIALS
WORKING HEIGHTS	FROM 27 TO 73 IN. (68.6 TO 185 CM). 2 IN. (5 CM) INCREMENT ADJUSTABLE HEIGHTS
REACH	12 FT (3.7 M). STACKABLE UP TO 3 UNITS HIGH FOR 24 FT (7.4 M) REACH*
PLATFORM	1/2" (12 MM) PLYWOOD, SLIP-RESISTANT WITH TRAPDOOR
CASTERS	5 IN. (13 CM) DOUBLE LOCKING HEAVY DUTY
STANDARDS	ANSI, CSA AND OSHA
MODEL	I-CISCH1
UPC	778300001804

AVAILABLE OPTIONS



GUARDRAILS SYSTEM*



SET OF 14" OUTRIGGERS*



SET OF 4 CASTERS WITH LEVELING JACKS



39" HIGH EXTENSION



CLIMB-N-GO MOTORIZED SYSTEM



SET OF 46" OUTRIGGERS*



SET OF LEVELING JACKS



SCAFFLOCK™ SAFETY BRAKES



TOOL SHELF



SET OF BASE PLATES



WWW.METALTECH.CO

1 800 363-7587