


USG DONN® BRAND IDENTITEE® DXI™ ACOUSTICAL SUSPENSION SYSTEM


USG Donn® Brand Identitee® DXI™
Acoustical Suspension System/USG
Halcyon™ Acoustical Panels

TO ORDER SAMPLES, GO TO USG.COM OR CGCINC.COM


STANDARD COLORS¹




ADVANTAGE COLORS¹



PREMIUM COLORS



POWDER-COATED FINISH




FEATURES AND BENEFITS

- Narrow-profile grid system with double 1/8" reveal.
- Seamless reveal at intersections.
- Meets or exceeds all national code requirements including seismic.
- Compatible with USG Logix™ Integrated System.
- Custom colors available.
- ICC-ES evaluated for seismic installations (ESR-1222).
- G30 hot-dipped galvanized steel body and cap inhibits red rust.
- All USG Donn® Brand Identitee® DXI™ items have High Recycled Content (HRC).
- Metric sizes available.
- Proprietary cap lance allows a variety of color and coating options to meet unique project requirements.
- USG Donn® Brand Identitee® DXI™ Suspension System is part of the Ecoblueprint™ portfolio – meeting today's sustainability standards. For sustainability documentation go to USG.com or CGCInc.com.


APPLICATIONS

- All interior general-use areas
- USG Logix™ Integrated System

PROFILE



EDGE DETAIL



USG DONN® BRAND IDENTITEE® DXI™ ACOUSTICAL SUSPENSION SYSTEM


ORDER SAMPLES/LITERATURE
USG: usg.com or samplitt@usg.com
CGC: contact Sales Representative
TECHNICAL SERVICES
800 USG.4YOU (874-4968)

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com




Declare® Labels on select finishes, see usg.com for more details and documentation.

9/16" TEE SYSTEM® Main Tee



Cross Tee



ASTM Class	Length	Height	Item No.	Fire Rating	Seismic Design Category		Rated Load ^{2,4}		
					IBC	ICC-ES Evaluated Installation	4' Hanger Spacing	5' Hanger Spacing	6' Hanger Spacing
Intermediate Duty	12' 3600 mm	1-13/16" 46.5 mm	DXI24HRC 	Class A 	A-C	7/8" Molding ACM7 Clip 	12 lb./ LF	7.3 lb./ LF	4.2 lb./ LF
Heavy Duty	12' 3600 mm	1-13/16" 46.5 mm	DXI26HRC 	Class A	A-F	7/8" Molding ACM7 Clip	16 lb./ LF	9.1 lb./ LF	5.2 lb./ LF
Heavy Duty	10' 10' 12' 8'	1-13/16" 46.5 mm	DXIH120HRC DXIH120/27HRC DXIH2412/20HRC DXIH96/21HRC 	Class A	A-F	7/8" Molding ACM7 Clip	16 lb./ LF	9.1 lb./ LF	5.2 lb./ LF
—	21"	1-13/16" 46.5 mm	DXI2124 	Class A	—	—	—	—	—
—	27"	1-13/16" 46.5 mm	DXI2724 	Class A	—	—	—	—	—
—	30"	1-13/16" 46.5 mm	DXI3024 	Class A	—	—	—	—	—
—	42"	1-13/16" 46.5 mm	DXI4224 	Class A	—	—	—	—	—
—	54"	1-13/16" 46.5 mm	DXI5424 	Class A	—	—	—	—	—
—	57"	1-13/16" 46.5 mm	DXI5724 	Class A	—	—	—	—	—
—	1'	1-13/16" 46.5 mm	DXI124 	Class A	—	—	—	—	—
—	2' 600 mm	1-13/16" 46.5 mm	DXI224HRC 	Class A	—	—	—	—	—
—	4' 1200 mm	1-13/16" 46.5 mm	DXI424HRC 	Class A	—	—	—	—	—
—	5' 1500 mm	1-13/16" 46.5 mm	DXI524HRC 	Class A	—	—	—	—	—
—	6'	1-13/16" 46.5 mm	DXI624 	Class A	—	—	—	—	—
—	8'	1-13/16" 46.5 mm	DXI 824 	Class A	—	—	—	—	—
—	USG Logix™	1-13/16" 46.5 mm	See USG Logix™ Guide IS268 	Class A	—	—	—	—	—

Low Emissions (VOC)
CDPH 01350 v1.2-2017 compliance on select finishes, see usg.com for more details and documentation.

High Recycled Content
USG classifies High Recycled Content as greater than 50%. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

USG DONN® BRAND IDENTITEE® DXI™ ACOUSTICAL SUSPENSION SYSTEM

ORDER SAMPLES/LITERATURE
USG: usg.com or samplit@usg.com
CGC: contact Sales Representative

TECHNICAL SERVICES
800 USG.4YOU (874-4968)

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com

30 YEAR LIMITED SYSTEM WARRANTY
• No Visible Sag
• Mold/Mildew Protection

HRC HIGH RECYCLED CONTENT

ECOBUEPRINT

Declare.

Declare® Labels on select finishes, see usg.com for more details and documentation.

MOLDING®



Wall Angle	Length	Item No.	Color
	12' 3600 mm	M9	Flat White Standard Advantage Premium
		M9HRC 	Flat White Standard Advantage Premium
	12' 3600 mm	M7	Flat White Standard Advantage Premium
		M7HRC 	Flat White Standard Advantage Premium
	12'	MS125	Flat White Standard Advantage Premium
		MS174	Flat White Standard Advantage Premium
	12'	MS174HRC 	Flat White Standard Advantage Premium
		MS174	Flat White Standard Advantage Premium
Face Sleeve	—	TFS-5®	—
Intersection Sleeve	—	TFS-5 DXI FC®	—

Low Emissions (VOC)
CDPH 01350 v1.2-2017 compliance on select finishes, see usg.com for more details and documentation.

High Recycled Content
USG classifies High Recycled Content as greater than 50%. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

USG DONN® BRAND IDENTITEE® DXI™ ACOUSTICAL SUSPENSION SYSTEM

ORDER SAMPLES/LITERATURE
USG: usg.com or samplitt@usg.com
CGC: contact Sales Representative

TECHNICAL SERVICES
800 USG.4YOU (874-4968)

**FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL**
usgdesignstudio.com
cgcdesignstudio.com



Declare® Labels on select finishes, see usg.com for more details and documentation.

PHYSICAL DATA/ FOOTNOTES

Product literature and samples

Data sheet: AC3281
USG Logix™ system guide: IS268
USG Logix™ architectural design guide: IS287
Sample: Z16276

Material

G30 hot-dipped galvanized steel body and cap. Baked-on polyester paint.

Installation

Install according to ASTM C636, ASTM E580, CISCA and USG requirements. Alternate installation methods may be used when approved by the authority having jurisdiction.

Online tools

usgdesignstudio.com or cgcdesignstudio.com

ICC Evaluation Service, LLC Report

Compliance
For areas under ICC jurisdiction, see ICC-ES Evaluation Report ESR-1222 for allowable values and conditions of use. Reports are subject to reexamination, revision and possible cancellation. Refer to usg.com for most current version.

Classified as Light, Intermediate or Heavy Duty when tested in accordance with ASTM C635.

Air diffusers

Request AC272-290.

Additional accessories

1. Load transfer bracket—use DXI/DXT26LTB.
2. Partition attachment—use UPAC.
3. Lift fixture clip—use LFC.

Notes

1. Custom color available. Upcharges apply to Standard and Advantage colors.
2. Load test data shows uniform load in lb./LF based on simple span tests in accordance with ASTM C635 deflection limit of L/360.
3. Available in metric.
4. Hanger wire spacing and location must be per the UL design.
5. Panels must be field-cut to size at the perimeter.
6. For seismic expansion joints.
7. For off-module intersections.
8. Metric items listed available with standard lead times. Other metric items available by RTQ.

Notice

The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

AC3281/rev. 2-23

© 2023 USG Corporation and/or its affiliates. All rights reserved. Printed in U.S.A.

Manufactured by
USG Interiors, LLC
550 West Adams Street
Chicago, IL 60661

The trademarks USG, CGC, AX, DONN, DXI, FINELINE, HALCYON, IDENTITEE, LOGIX, ZXLA, IT'S YOUR WORLD, BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

