

# USG ECLIPSE™/ECLIPSE™ HIGH-NRC ACOUSTICAL PANELS


CLIMAPLUS™ PERFORMANCE

USG Eclipse™ Acoustical Panels  
with ClimaPlus™ Performance, and  
USG Donn® Brand Identitee® DXI™  
Acoustical Suspension System

## TO ORDER SAMPLES, GO TO [USG.COM](http://USG.COM) OR [CGCINC.COM](http://CGCINC.COM)

See individual items for color availability.

### STANDARD COLORS



Flat White 050   Parchment 103   Manila 246   Taupe 107   Straw 143   Sandstone 090

### ADVANTAGE COLORS



Beige 142   Silvertone 052   Mist 053

## FEATURES AND BENEFITS

- Elegant, fine-textured visual.
- Excellent noise reduction (up to NRC-0.75).
- Balanced Acoustics. High-NRC and High-CAC.
- ClimaPlus™ 30-year limited system warranty against visible sag, mold and mildew.
- USG Eclipse™ Acoustical Panels is part of the Ecoblueprint™ portfolio — meeting today's sustainability standards. For sustainability documentation go to [USG.com](http://USG.com) or [CGCInc.com](http://CGCInc.com).

## APPLICATIONS

- Offices
- Conference areas
- Healthcare (HIPAA requirements)
- Retail stores

## SUBSTRATE

- Wet-formed mineral fiber

Fine-Textured Panel

# USG ECLIPSE™/ECLIPSE™ HIGH-NRC ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

ORDER SAMPLES/LITERATURE  
USG: usg.com or samplitt@usg.com  
CGC: contact Sales Representative

TECHNICAL SERVICES  
800.USG.4YOU (874-4968)

FOR MOST UP-TO-DATE  
TECHNICAL INFORMATION  
AND LEED REPORT TOOL  
usgdesignstudio.com  
cgcdesignstudio.com



PRODUCT CERTIFIED  
FOR LOW CHEMICAL  
EMISSIONS:  
ULCOM/GG  
UL2818



## USG ECLIPSE™ PANELS

## USG ECLIPSE™ HIGH-NRC PANELS

Edge	Panel Size	Fire Rating	Item No.	UL Classified			Color <sup>4</sup>	Grid Options	VOC Emissions	Anti-Mold & Mildew	Recycled Content <sup>1</sup>	Panel Cost
				NRC	CAC	LR <sup>2</sup>						
SQ 	2'x2'x3/4"	Class A	76575	0.70	35	0.86	White	A, B, C	Low		79%	\$\$
	2'x4'x3/4"		78575	0.70	35	0.86	White	A, B	Low		79%	\$\$
SLT 	2'x2'x3/4"	Class A	76775	0.70	35	0.86	White/ Colors	D	Low		79%	\$\$
	600x600x19		ME76775	0.70	35	0.86	White	D	Low		79%	\$\$
FL 	2'x2'x3/4"	Class A	76975	0.70	35	0.86	White/ Colors	E, F, G, H	Low		79%	\$\$
	600x600x19		ME76975	0.70	35	0.86	White	E, F, G, H	Low		79%	\$\$
SQ 	2'x2'x7/8"	Class A	76520	0.75	35	0.86	White	A, B, C	Low		80%	\$\$\$
	2'x4'x7/8"		76521	0.75	35	0.86	White	A, B	Low		80%	\$\$\$
SLT 	2'x2'x7/8"	Class A	76522	0.75	35	0.86	White	D	Low		80%	\$\$\$
	2'x4'x7/8"		76523	0.75	35	0.86	White	D	Low		80%	\$\$\$
FL 	2'x2'x7/8"	Class A	76524	0.75	35	0.86	White	E, F, G, H	Low		80%	\$\$\$
	2'x4'x7/8"		76525	0.75	35	0.86	White	E, F, G, H	Low		80%	\$\$\$

**Low Emissions**  
Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.2 - 2017 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at spot.ul.com.

**ClimaPlus™ Warranty Performance<sup>3</sup>**  
Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

**High Recycled Content**  
USG classifies High Recycled Content as greater than 50%. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

## GRID PROFILE OPTIONS

A USG DX*	B USG DXW™	C <sup>5</sup> USG Centricitee™ DXT™	D USG DX*	E USG Centricitee™ DXT™	F USG Fineline* DXF™	G USG Fineline* 1/8 DXFF™	H USG Identitee* DXI™

## PHYSICAL DATA

**Product literature**  
Data sheet: SC1812

**ASTM E1264 classification**  
Type III, Form 1, Pattern EI

**ASTM E84 and CAN/ULC S102 surface-burning characteristics**  
Class A  
Flame spread: 25 or less  
Smoke developed: 50 or less

**Imperial weight**  
1.10-1.19 lb./sq. ft. (Class A panels and tile)

**Metric weight**  
5.07 kg/m<sup>2</sup> (Class A panels)

**Thermal resistance**  
R-2.0 (Class A)

**Maximum backloading**  
See USG 30-Year Limited System Warranty Commercial Applications (SC2102).

**Online tools**  
usgdesignstudio.com or cgcdesignstudio.com

**Maintenance**  
Can be cleaned easily with a soft brush or vacuum.

**Metric sizes available**  
Contact sales for minimum quantities and lead times.

- Notes**
- For details, see USG Sustainability tool at usgdesignstudio.com or cgcdesignstudio.com.
  - LR values shown as averages.
  - For details, see USG 30-Year Limited System Warranty Commercial Applications (SC2102).
  - See Colors selector for more information. Metric: white only.
  - Maximum 2'x2' with SQ edge panels.

**Notice**  
The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC1812/rev. 2-23  
© 2023 USG Corporation and/or its affiliates. All rights reserved. Printed in USA

Manufactured by USG Interiors, LLC  
550 West Adams Street  
Chicago, IL 60661

The trademarks USG, CGC, CENTRICITEE, CLIMAPLUS, DONN, DX, DXF, DXFF, DXI, DXLF, DXLT, DXT, DXW, ECLIPSE, FINELINE, IDENTITEE, IT'S YOUR WORLD. BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

