

SNOOC™

LIGHTING CREATOR



IP66

AUSTIN

A light, a world of possibilities

Austin – AU

LUMINAIRE COMPONENTS

- Cast aluminum body.
- IP66 certified optics.

WARRANTIES

- Lifetime warranty on cast aluminum components.
- 5-year warranty against paint peeling.
- 10-year warranty on LED lighting system and 5-year warranty on converter.
- Replacement parts available for a minimum of 20 years.

PHOTOMETRY

Most optical systems offer photometric measurements that allow for the distributions mentioned further. For the required data (in standard IES format) to calculate a scheme for a lighting project, please visit our website at www.snoc.com



ORDER EXAMPLE

AU0030D10W50EBK

(AU, 30W LED, 3000K, 120V, no optics, Hyper-extensive, type V, clear tempered glass, black)

MOUNTING

00 : on post or 3" tenon

SOURCE

Light emitting diodes

Power	Color
30 : 30W	A : Amber
40 : 40W	D : 3000K
50 : 50W	L : 4000K
60 : 60W	
75 : 75W	
100 : 100W	

TENSION

1 : 120 to 277V
5 : 347V

LED BOARD

N : Regular
W : Hyper-extensive *Type III and V only*

TYPE

1 : I **3** : III **5** : V
2 : II **4** : IV

GLASS

0 : None (*LED regular only*)
E : Clear tempered glass
B : Opaline polycarbonate (*type V only*)
D : Opaline acrylic (*type V only*)

FINISH

AT : Anthracite	DZ : Textured bronze
BK : Black	FG : Forest green
BZ : Brown	PE : Pewter
DB : Textured black	PG : Pine green
DS : Silver	WH : White
DW : Textured white	XX : On request

OPTIONS

TPR : Twist-lock adapter
TP5 : 3 PIN + 2 dimmers
TP7 : 3 PIN + 2 dimmers + 2 controls
F : Fuses
D : 0-10 volt dimming