



## GSA EASY SAND N FILL

### PRODUCT DESCRIPTION:

GSA Easy Sand N Fill is a preparation coat designed to be applied to porous surfaces and once sanded gives a smooth surface suitable for coating with both water or solvent borne gloss topcoats.

**APPLICATIONS:** Ideal for use on MDF, interior bare timber, plasterboard, brick and cement rendered (cement render must have cured for a minimum of 28 days prior to application). **Not generally used on previously painted surfaces and not recommended for the overcoating of enamel paints.**

**SURFACE PREPARATION:** Surfaces are to be suitably prepared in accordance with proper trade practices. Ensure the surface is clean, dry and free from dust, dirt, grease, oil, smoke stains, cooking residues, polishes and materials detrimental to the finish and adhesion of the new paint. If mould is present, clean surface with a suitable mould treatment as per manufacturer's instructions. Fill surface holes with a suitable GSA filler and sand lightly to an even finish. All loose, peeling or flaking material must be removed. Test soundness of previously painted surfaces by cutting a small X in the paint with a sharp blade. Stick a piece of tape firmly over the X and pull off. If the paint pulls away, the surface is unsound. Repeat at random in a number of areas. Unsound surfaces should be completely removed. Sand the surface smooth and remove all dust. Sand enamel painted surfaces to remove gloss. Ensure all new cement and concrete surfaces are fully cured prior to painting. Typically this may take a minimum of 4-6 weeks. Ensure concrete surfaces are free from any bond breakers, formwork release agents and curing compounds. Timbers that contain high tannin levels may cause staining of the finish. If overcoating with a water based product then an oil based sealer or other suitable tannin blocking sealer is recommended.

**DIRECTIONS:** Stir well with a broad paddle. Brush is the preferred method of application but roller and spray can be used. Thinning is not generally recommended as it can affect the filling properties but up to 100ml per litre can be added for spraying or application to very porous surfaces.

**COVERAGE:** up to 14m<sup>2</sup> per litre. This is subject to surface porosity and texture.

**DRYING (@25°C <50%RH) :** Touch Dry 30min, Recoat 2 hours, Sanding 3 hours. Allow longer in colder or more humid temperatures. Coating thickness will also affect the drying time so allow longer before sanding for thicker applications. **Do not apply if the temperature is below 10°C or above 35°C.**

**PACK SIZE:** 4l - code: 052 10L - code: 053

**CLEAN UP:** Water and detergent, Dried spots can be removed with Pacer F57 All purpose thinners. **Do not dispose of waste paint or cleaning effluent through the drain.**



## GSA EASY SAND N FILL

**Storage:** Store between 5°C and 25°C in cool dry conditions. Protect from low temperatures and frost.

**Health & Safety:** Safety Data Sheet available from [www.cwbrands.com.au](http://www.cwbrands.com.au)

Non-hazardous product **Keep Out Of Reach Of Children.** If swallowed seek medical advice immediately or contact the **Poisons Information Center on 13 11 26.**

Spills and leaks can be contained with absorbent material such as sand, earth or saw dust.

**DISPOSAL:** Dispose of in accordance with local, state and federal regulations

### Disclaimer

CW Brands Pty Ltd believes that the information in this technical data sheet is an accurate description of the typical uses of the product. The data and statements are based on our research and development work and is to the best of our knowledge true and accurate. The user must ensure of the product(s) in their application prior to use in particular to determine its performance, efficiency and safety. The use of this product is beyond the manufacturer's control, and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Products conform solely to the information contained in this and other related CW Brands Pty Ltd publications.

CW Brands Pty Ltd reserves the right to make changes to specifications and information related to the products at any time. Users are asked to check that the literature in their possession is the latest issue. Statements contained herein should not be considered as a warranty of any kind, expressed or implied in describing the performance or suitability of the product for a particular application. No liability is accepted for infringement of any patents or any other intellectual property right.