

MINERAL TURPENTINE

TECHNICAL DATA SHEET

Phone: (09) 25000 91

Fax: (09) 2500<u>0 92</u>

Email: sales@pacer.co.nz

DESCRIPTION:

Mineral Turpentine is used for thinning oil based paints and as a degreasing and cleaning solvent. Mineral Turpentine is also suitable for spot cleaning purposes to remove tar, oil and grease when rinsing with water is not necessary.

DIRECTIONS:

Thinning: Use in accordance with the paint manufacturer's recommendations.

Cleaning: Before use test the colourfastness of the surface in an inconspicuous area. Spray onto the surface to clean, and then wipe dry.

APPLICATIONS:

Paint thinning and cleaning brushes and equipment after painting

PROPERTIES:

Clear liquid with sharp smell. Flash point of 31°C

Available Sizes:









MT20

MT9

WARNING

Extremely flammable liquid and vapour H227 H304 May be fatal if swallowed and enters airways

H317 May cause an allergic skin reaction

Harmful if inhaled H332









WARNING



Body Shop









WARNING: HIGHLY FLAMMABLE LIQUID AND VAPOUR. Small amounts of liquid aspirated into the lungs during ingestion, or from vomiting, may cause chemical pneumonitis or pulmonary oedema. Ingesting any amount of this product will result in dizziness, headaches, nausea and tracheal burning. Irritating to the eyes but will not permanently damage the eye tissue. Irritating to the skin with prolonged exposure. It may result in dryness and cracking. Irritating to the respiratory tract. Exposure to large concentrations over an extended period will result in muscle weakness, blurred vision, headaches, nausea and possible loss of consciousness

SAFETY PRECAUTIONS: Keep well away from heat, sparks and open flame. Keep container well closed. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves and eye/face protections. Do not eat, drink or smoke whilst using. Avoid breathing vapour. Use with adequate ventilation. Dispose empty container in a safe manner. In case of fire, use CO₂ / Dry Powder for extinction. Collect spillage.

FIRST AID:

Hold eves open and flush with water for at least 15 minutes.

Immediately re move contaminated clothing and wash skin and clothes thoroughly with running water

Ingestion

Do not induce vomiting. Rinse mouth with water. If victim not breathing begin artificial respiration. Obtain medical attention.

Remove to fresh air. If breathing is difficult, seek medical attention immediately immediately.

If medical advice is needed have the product container/label at hand. In an emergency phone the National Poison Centre. (24 hrs.): 0800 POISON[764 766]. UN 1300. Class 3. PG II. Hazchem 3[V].

OUR VISION AND MISSION

To be the leading value-based provider to the market. We have a dedicated team to achieve excellence for our customers and a philosophy of total quality. We conduct business and create relationships in an ethical and sustainable manner with customers, our community and the environment. The value we provide our customers is the opportunity to increase profit through lower cost solutions that do not sacrifice quality or service.

ENVIRONMENTAL POLICY

Pacer is committed to leading the industry in minimising the impact of its activities on the environment. The key points of our strategy to achieve this are: Purpose built premises utilising energy efficient technology and rain water collection. Actively promoting recycling both internally and amongst our customers and suppliers. To develop and promote a product range to minimise the environmental impact of our products. We are constantly evaluating and looking at substituting to a more environmentally friendly composition of raw materials for our products. To meet or exceed all the environmental legislation that relates to our industry.

DISCLAIMER

The technical data and information provided, including the recommendations for applying & using our products, is given in good faith based on our current knowledge and experience and is believed to be accurate when applied under 'normal' conditions. In practice, the materials, surfaces or conditions are so varied that no warranty regarding the working results or any liability or quarantee can be inferred either from this information nor from a verbal consultation. It is recommended that the user makes his or her own tests to determine the suitability of the product for their own requirements