



	RAPID REPAIR FILLER	FLEXIBLE WOOD FILLER	UNIVERSAL FINE FILLER	SUPER EXTERIOR FILLER
INTERIOR USE	Yes	Yes	Yes	Yes
EXTERIOR USE	Yes	Yes	Yes	Yes
TIMBER USE	Yes	Yes Ideal for staining, varnishing & painting	Yes Perfect high gloss result	Yes
SINGLE APPLICATION FILLING DEPTH	5mm	10mm / max 20mm in two layers	2mm	50mm / max 100mm in two layers
DRYING TIME				
Touch Dry	2 min (2mm)			
Sand	15 mins	1 hr (2mm)	4 hrs	24 hrs
Paint (Water base)	15 mins	1 hr (2mm) / 3 hrs (10mm)	4 hrs	2 hrs (no sanding)
Paint (Oil base)	15 mins	3 hrs (10mm)	4 hrs	24 hrs
FINISH	Smooth, white	Smooth, natural pine	Super smooth, white	Slightly coarse, light grey
SANDABILITY	Easy to sand	Easy to sand	Easy to sand	Yes, after 24hrs
NAIL/SCREW ACCEPTANCE	Yes	Yes	No	Yes, also drillable
SIZES	330g tube 1L pot	500ml pot	330g tube 1L pot 2.5 pot	1L pot 2.5L pot 10L pot