

Features/特性

- Convection Cooled Operation.
- Low power consumption high reliability.
- Short circuit /Over Voltage/Over Current/Over Temp Protection.
- Class 2 PTC output protection for each port
- Individual status LED indicator for each output

Applications/应用领域

CCTV Camera, IP Camera, PTZ, IR Illuminator, Video process, DVR, Access Control, etc.

Parameters Table/参数表

Model Number	PS-DC10A09E
Item	CCTV Power Supply Box
Input Voltage	AC110~240V 50/60HZ
Output	DC 12V 10A 9Channel
Efficiency	≥82%
Fuse Type	PTC Fuse
Fuse Rating	1.25A
Operating Temperature	-10~40°C
Carton Dimension	350*310*350mm
Carton Weight	5pcs/carton; 9.5KG
Size	240*260*60mm/1.7KG
Color	White
Load regulation	A ±5%
life	10000 hours



Please read this manual before using your voltage source. It is recommended that you return your power supply to a qualified dealer for any service or repair. Incorrect connection may cause fire or electric shock.

For more information on the product, please visit our website www.centropower.com and search for the model indicated at the beginning .

For more information or questions, call us at 0755-23200933.



CENTROPOWER[®]

China Office:4th Floor; Chashu 1#,Area B,HuaFeng 1st Technology,Gushu Sanwei,Xixiang,Shenzhen Phone:0755-23200933 USA Office:15322 E Valley Blvd,City of Industry,CA91746 Phone:(626)391-8868 Website:www.centropower.com Email:info@centropower.com



Product image/产品图片

