

Manual CCTV power supply

Model:
PS-DC20A18E



Features/特性

- Convection Cooled Operation.
- Low power consumption high reliability.
- Short circuit /Over Voltage/Over Current/Over Temp Protection.
- Class 2 PTC output protection for each port
- Individual status LED indicator for each output

Applications/应用领域

CCTV Camera, IP Camera,
PTZ, IR Illuminator, Video process,
DVR, Access Control , etc.

Parameters Table/参数表

| | |
|-----------------------|----------------------------|
| Model Number | PS-DC20A18E |
| Item | CCTV Power Supply Box |
| Input Voltage | AC110 or 220V 5A 50/60HZ |
| Output | DC 12V 20A (MAX) 18Channel |
| Efficiency | ≥80% |
| Fuse Type | PTC Fuse |
| Fuse Rating | 1200MA |
| Operating Temperature | -10~40℃ |
| Carton Dimension | 350*310*350mm |
| Carton Weight | 10pcs/carton |
| Size | 240*260*60mm |
| Color | White |
| Load regulation | A ±5% |
| life | 10000 hours |

Product image/产品图片



NOTE:

Please read this manual before using your voltage source. It is recommended that you return your power supply to a qualified dealer for any service or repair. Incorrect connection may cause fire or electric shock.

For more information on the product, please visit our website www.centropower.com and search for the model indicated at the beginning .

For more information or questions, call us at 0755-23200933.



CENTROPOWER®

China Office: 4th Floor, Chashu 1#, Area B, HuaFeng 1st Technology, Gushu Sanwei, Xixiang, Shenzhen

Phone: 0755-23200933

USA Office: 15322 E Valley Blvd, City of Industry, CA91746 Phone: (626)391-8868

Website: www.centropower.com Email: info@centropower.com