



PS-DC5A04B

CCTV AC to DC 12V, 5A 4CH Without Battery With Lock Power Supply Box



Model Number	PS-DC5A04B
Input Voltage :	AC 110 ~ 220V
Input Voltage Frequency	50/60Hz CSE1205A-D4UPS
Output Voltage :	DC 12V / 13.8V
Total Output Current :	5A
Total Outputs :	4 channels
Fuse Type :	PTC (Resettable) Never need to replace.
Fuse Rating :	1.6A
Remark	7AH acid battery including
Features :	



Centro Technology Limited

Thermal Cutoffs Protection (TCO): each output has independent PTC fuse and LED indicator, when problem occurs, only affect the independent output, other outputs still working.

Short circuit protection: when short condition occurs, independent PTC fuse will open the circuit, when condition removed, PTC fuse will automatically back to close.

High voltage protection: when high voltage occurs, the surge protection will be hit through to protect the connected device.

Over Current protection: when over current occurs, the power supply will automatically switch to self-protection status, when condition removed, then switch back to normal.

Application :	CCTV Camera, IP Camera, PTZ, IR Illuminator, DVR, LED Driver, Access Control , etc.
Packing Dimension :	220 x 180 x80 (mm)
Net Weight :	1.4KG
Carton Dimension:	53*30*40CM 10PCS /Carton
Certification:	CE, Rohs