

### Fateruse/特性

- Support PoE applications in Gi gabit Ethernet environments.
- Auto-Sensing Algorithm enables taking power from IEEE802.3af/at PSE.
- Splits the 48VDC power over RJ45 Ethernet cable into different DC output.
- Support wide input voltage range 36Vdc to 57Vdc.
- Maximum power output up to 30W.
- Adjustable output 5VDC,9VDC,12VDC,18VDC.
- Thermal cut off.
- Short circuit protection.
- High efficiency DC/DC converter.
- LED indicators for power input indication.

## Parameters Table/参数表

Model Number	PoE-S911
Item	Switching Power Supply
Input Voltage	AC100~240V 50/60HZ
Output	DC 12V 5A (MAX)
Efficiency	≥82%
Fuse Rating	5000MA
Operating Temperature	-10~40℃
Carton Dimension	470*280*300mm
Carton Weight	100pcs/carton
Size/Net Weight	57*37*26mm
Color	Metal color
Load regulation	A ±5%
life	15000 hours
Certification	CE,RoHS, FCC,UL, etc.

#### NOTE:

Please read this manual before using your voltage source. It is recommended that you return your power supply to a qualified dealer for any service or repair. Incorrect connection may cause fire or electric shock.

For more information on the product, please visit our website www.centropower.com and search for the model indicated at the beginning .

For more information or questions, call us at 0755-23200933.



# **CENTROPOWER**®

China Office:4th Floor: Chashu 1#,Area B,HuaFeng 1st Technology,Gushu Sanwei,Xixiang,Shenzhen Phone:0755-23200933 USA Office:15322 E Valley Blvd,City of Industry,CA91746 Phone:(626)391-8868 Website:www.centropower.com Email:info@centropower.com

# Applications/应用领域

CCTV Camera, IP Camera, PTZ, IR Illuminator, Video process, DVR, Access Control , etc.

## Productimage/产品图片



POWER+DATA IN:Connect to the PoE Switch or PoE Injector with a CAT5 UTP



VOLTAGE SWITCH :Choose the DC output voltage of 5V, 9V or 18V by turning , 12V the switch to the left or right.