

# LED Wall Pack Light 30W







 WWW.GGJIA-LED.COM

 Tel: +1(626)977-6424

 E-mail: sales@ggjia-led.com

/



#### Features:

- Integrated 120-277V photosensor optional.
- Die-cast aluminum housing is good for heat dissipation.
- ETL approved for wet locations.
- Surface mounts to standard junction box.
- · Instant energy savings and potential rebate eligibility.
- No RF interference, No IR/UV radiation ,no mercury pollution.
- Long 50,000 hour rated life.
- Minimizes replacements and labor costs.
- Robust design protects the LEDs to withstand harsh outdoor environments.
- · Easy installation and retrofit application

### Specifications:

Model	RMS-L2118-30W
Power	30W
Luminous Flux	3600lm
Luminous Efficacy	120lm/w
Light Source	Epistar LED
Operation Temp	-40°C to +45°C
СТТ	5000K
CRI	>80
Life Span	50,000 hours
Voltage	100-277VAC/50-60HZ
Beam Angle	120°
РТ	>0.95
Warranty	5 Years







Die Casting Aluminum Heat Sink ADC12







LED driver, high reliable, offer 5 years warranty



## Dimension:

#### Unit: mm





# Application:

- Site Lighting
- Security Lighting
- Pathways
- Entrances
- Perimeters

