PowerEdge R750xs

D&LLTechnologies

Spec Sheet

Purpose-built 2U for growing scale-out solutions

The Dell EMC PowerEdge R750xs, with 3rd generation Intel® Xeon® Scalable processors, is purposefully designed with distinctive, customer-defined requirements to deliver enterprise performance for scale-out environments.



Innovate at scale with challenging and emerging workloads

The new Dell EMC PowerEdge R750xs is a 2U, dual-socket, feature-optimized server with an ideal selection of CPU, I/O, and storage performance for scale-out environments. With it, you can:

- Add additional power and cores: Up to two 3rd generation Intel® Xeon® Scalable processors, up to 32 cores per socket
- · Accelerate in-memory workloads: Up to 16 DDR4 RDIMMS, 3200 MT/sec
- Improve throughput, reduce latency: With up to 5 PCIe Gen4 slots, OCP 3.0 for network cards, and SNAP I/O support
- Include flexible storage: Up to 12x 3.5" SAS/SATA HDDs or SSDs; or up to 16x 2.5" SAS/SATA HDDs or SSDs, and 8 NVMe drives
- · Enable virtualization, medium VM density or VDI, and software-defined storage node workloads

Increase efficiency and accelerate operations with autonomous collaboration

The Dell EMC OpenManage systems management portfolio tames the complexity of managing and securing IT infrastructure. Using Dell Technologies' intuitive end-to-end tools, IT can deliver a secure, integrated experience by reducing process and information silos in order to focus on growing the business. The Dell EMC OpenManage portfolio is the key to your innovation engine, unlocking the tools and automation that help you scale, manage, and protect your technology environment.

- Built-in telemetry streaming, thermal management, and RESTful API with Redfish offer streamlined visibility and control for better server management
- Intelligent automation lets you enable cooperation between human actions and system capabilities for added productivity
- Integrated change management capabilities for update planning and seamless, zero-touch configuration and implementation
- Full-stack management integration with Microsoft, VMware, ServiceNow, Ansible and many other tools for onpremise, edge and cloud environments

Built-in proactive resilience through a complete portfolio of solutions

From the silicon and supply chain all the way to asset retirement, know that your servers are safe and secure with innovative Dell EMC and Intel technologies. We give you the confidence of cyber resilience with enterprise class security that minimizes risk for any organization, from small business to hyperscale.

- Start strong with platform security features, even before the server is built, including Secured Component Verification and Silicon Root of Trust
- Stay strong with continuous innovations that bolster cyber resilience, like OpenManage Secure Enterprise Key Manager and Automatic Certificate Enrollment
- Outmaneuver threats with intelligence, automation, and recovery tools that include iDRAC9 Telemetry, BIOS live scanning, and Rapid OS recovery

PowerEdge R750xs

The Dell EMC PowerEdge R750xs offers compelling performance, highspeed memory and capacity, I/O bandwidth and storage to address data requirements – Ideal for:

- Virtualization
- Medium VM density or VDI
- Software-defined storage node

Features	Technical Specifications		
Processor	Up to two 3rd Generation Intel Xeon Scalable processors with up to 32 cores		
Memory	16 DDR4 DIMM slots, supports RDIMM 1 TB max, speeds up to 3200 MT/s		
	Supports registered ECC DDR4 DIMMs only		
Storage controllers	 Internal controllers: PERC H345, PERC H355, PERC H745, PERC H755, PERC H755N, HBA355i, S150 Internal Boot: Internal Dual SD Module, Boot Optimized Storage Subsystem (BOSS-S2): HWRAID 2 x M.2 SSDs, USB 		
	External PERC (RAID): PERC H840, HBA355e		
Drive Bays	Front bays:		
	 0 drive bay Up to 8 x 3.5-inch SAS/SATA (HDD/SSD) max 128 TB 		
	Up to 12 x 3.5-inch SAS/SATA (HDD/SSD) max 120 TB		
	 Up to 8 x 2.5-inch SAS/SATA/NVMe (HDD/SSD) max 61.44 TB 		
	Up to 16 x 2.5-inch SAS/SATA (HDD/SSD) max 122.88 TB		
Power Supplies	• Up to 16 x 2.5-inch (SAS/SATA) + 8 x 2.5-inch (NVMe) (HDD/SSD) max 184.32 TB		
	Rear bays:		
	Up to 2 x 2.5-inch SAS/SATA/NVMe (HDD/SSD) max 15.36 TB 600W Platinum Mixed Mode (100-240Vac or 240Vdc) hot swap redundant		
	 800W Platinum Mixed Mode (100-240Vac or 240Vdc) hot swap redundant 800W Platinum Mixed Mode (100-240Vac or 240Vdc) hot swap redundant 		
	 1100W Titanium Mixed Mode (100-240Vac or 240Vdc) hot swap redundant 		
	1400W Platinum Mixed Mode (100-240Vac or 240Vdc) hot swap redundant		
0	1100W -48Vdc hot swap redundant (CAUTION: only works with -48Vdc to -60Vdc power input)		
Cooling options	Air cooling Standard fans/High performance Silver fans/High performance Cold fans		
Fans	 Standard fans/High performance Silver fans/High performance Gold fans Up to six hot swap fans 		
Dimensions	• Height – 86.8 mm (3.41 inches)		
	• Width – 482.0 mm (18.97 inches)		
	Depth – 707.78 mm (27.85 inches) – without bezel		
	721.62 mm (28.4 inches) – with bezel		
Form Factor	2U rack server		
Embedded Management	iDRAC9 iDRAC Service Module		
	iDRAC Direct		
	Quick Sync 2 wireless module		
Bezel	Optional LCD bezel or security bezel		
OpenManage Software	OpenManage Enterprise		
	OpenManage Power Manager plugin		
	OpenManage SupportAssist plugin OpenManage Update Manager plugin		
Mobility	OpenManage Mobile		
Integrations and Connections	BMC Truesight	IBM Tivoli Netcool/OMNIbus	
U U	Microsoft System Center	IBM Tivoli Network Manager IP Edition	
	OpenManage Integrations	Micro Focus Operations Manager	
	Red Hat Ansible Modules	OpenManage Connections	
	VMware vCenter and vRealize Operations Manager	Nagios Core	
Socurity	Cryptographically signed firmware	Nagios XI	
Security	Cryptographically signed ilrmware Secure Boot		
	Secure Erase		
	Silicon Root of Trust		
	System Lockdown (requires iDRAC9 Enterprise or Datacenter)		
	TPM 1.2/2.0 FIPS, CC-TCG certified, TPM 2.0 China Natio	onZ	
Embedded NIC Network Options	2 x 1 GbE LOM 1 x OCP 3.0		
GPU Options	Not supported		
Ports	Front Ports	Rear Ports	
	1 x iDRAC Direct (Micro-AB USB) port	• 1 x USB 2.0	
	• 1 x USB 2.0	• 1 x Serial (optional)	
	• 1 x VGA	• 1 x USB 3.0	
		• 2 x Ethernet	
	Internal Ports	• 1 x VGA	
	1 x USB 3.0 (optional)		
PCle	Up to 5 x PCIe Gen4 slots + 1 x PCIe Gen3 slots		
	3 x16 Gen4 low profile		
	2 x16 Gen4 low profile (optional)		
	 1 x8 Gen3 (x4 lane) low profile 		

Features	Technical Specifications	
Operating System and Hypervisors	Canonical Ubuntu Server LTS	
	Citrix Hypervisor	
	Microsoft Windows Server with Hyper-V	
	Red Hat Enterprise Linux	
	SUSE Linux Enterprise Server	
	VMware ESXi	
	For specifications and interoperability details, see Dell.com/OSsupport.	
OEM-ready version available	From bezel to BIOS to packaging, your servers can look and feel as if they were designed and built by you. For more information, visit Dell.com/OEM.	

Recommended support and services

Dell ProSupport Plus for critical systems or Dell ProSupport for premium hardware and software support for your PowerEdge solution. Consulting and deployment offerings are also available. Contact your Dell representative today for more information. Availability and terms of Dell Services vary by region. For more information, visit www. delltechnologies.com/Services.

Dell Technologies on demand

Consume technology, infrastructure and services any way you want with Dell Technologies on Demand, the industry's broadest end-to-end portfolio of flexible consumption and as-a-Service solutions. For more information, visit: www. delltechnologies.com/ondemand.

Discover more about PowerEdge servers



Learn more about our

PowerEdge servers



Learn more about our systems management solutions







Follow PowerEdge servers on Twitter



Contact a Dell Technologies Expert for Sales or Support

© 2022 Dell Inc. or its subsidiaries. All Rights Reserved. Dell, EMC and other trademarks are trademarks of Dell Inc. or its subsidiaries. Other trademarks may be trademarks of their respective owners. June 2022

D&LLTechnologies