ADJ. ALUMINUM GANTRY CRANE WITH DUAL TIRE PNEUMATIC CASTERS - AHA-4-12-10-PNU *** ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE *** ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON 144" -120 1/4" -4 3/16" -REMOVABLE PIN 126 1/4" FOR HEIGHT **ADJUSTMENT** 112 1/8" MIN 142 1/8" MAX 104 1/8" MIN 134 1/8" MAX 17 1/2"**→** 3D VIEW 5 7/8" TIRE Ø 15 1/2" WIDTH 39 13/16" 114 5/8" 57 9/16' 149 5/8" 73 1/16" -**DIMENSION TOLERANCE ± 1/4"** I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS SPECIAL FEATURES STANDARD FEATURES REPRESENTED SATISFIES DESIGN AND DIMENSION REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION MODEL NUMBER IS AHA-4-12-10-PNU NONE CAPACITY IS 4,000 LBS. COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE Ρ AND LOCAL REGULATIONS AND STANDARDS **BASE WIDTH IS 73 1/16"** R UNITS REQUIRING APPROVAL DRAWINGS OR MAX OVERALL HEIGHT IS 142 1/8" MODIFIED ARE NON-RETURNABLE I-BEAM HEIGHT IS 8" [] As drawn [] As marked I-BEAM WIDTH IS 43/16" Signed: Date: OVERALL I-BEAM LENGTH IS 144" USABLE I-BEAM LENGTH IS 120 1/4" Printed Name: ADJUSTABLE UNDER I-BEAM HEIGHT LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING 104 1/8" MIN DISTRIBUTOR'S NAME: 134 1/8" MAX W.O.# X VESTIL MANUFACTURING HEIGHT IS ADJUSTABLE IN 6" INCREMENTS

HEIGHT IS ADJUSTABLE IN 6" INCREMENTS

(4) Ø 15 1/2" DUAL TIRE PNEUMATIC CASTERS

(SWIVEL WITH (4) LOCKING POSITIONS)

-PNU MODELS ARE 12" TALLER THAN STANDARD

AHA UNITS OF THE SAME HEIGHT DESIGNATION

ALUMINUM CONSTRUCTION

DISTRIBUTOR'S NAME:

VESTIL MANUFACTURING

DRAWN BY:

MTS

DATE:

01/29/2021

SALES: X

REFERENCE: X

QUOTED LEAD TIME: X

QUOTE #

QUOTE #

QUOTE #

X

QUOTE #

QUO