## APPROX WEIGHT: 86 lbs. ALUMINUM SHEET DECK PLATFORM TRUCK - ASD-2460 \*\*\* ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE \*\*\* ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON 64 5/8' 22 15/16" 24" 37 1/8" I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS REPRESENTED SATISFIES DESIGN AND DIMENSION 10" REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION P Ø 5" X 2" COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE Ρ POLY-ON-STEEL SWIVEL AND LOCAL REGULATIONS AND STANDARDS. R STANDARD FEATURES **CASTERS** ALL SPECIAL UNITS ARE NON-RETURNABLE 0 **MODEL NUMBER IS ASD-2460** 1 As drawn [ ] As marked V CAPACITY IS 3,600 LBS. Ø 5" X 2" FOR INTERNAL USE ONLY PROJECT SIGN OFF Α Signed: Date: **DECK WIDTH IS 24 INCHES** POLY-ON-STEEL SWIVEL **DECK LENGTH IS 60 INCHES** LEAD TIME WILL START UPON RECEIPT **CASTERS SALES** PLATFORM HEIGHT IS 10 INCHES OF SIGNED APPROVAL DRAWING FNG. POLY ON STEEL CASTERS DISTRIBUTOR'S NAME: 2 - 5 x 2 RIGID FAB. W.O.# X VESTIL MANUFACTURING 2 - 5 x 2 SWIVEL POWER DRAWN BY: CA HANDLE WIDTH IS 22 15/16 INCHES SALES: X DATE: 07/25/2011 WELDED ALUMINUM CONSTRUCTION reference: X SCALE: 1:14 FILE NAME: SPECIAL FEATURES REMOVABLE HANDLE QUOTED LEAD TIME: X SMOOTH ALUMINUM SHEET DECK SURFACE NONE QUOTE # 33-007-035-001 Χ