ELECTRIC HYDRAULIC SCISSOR LIFT TABLE, PARTIAL STAINLESS STEEL - EHLT-4848-2-43-PSS APPROX WEIGHT: 726.38 lbs. *** ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE *** ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON **ELECTRIC TOEGUARDS (STOPS** 43" TABLE FROM LOWERING IF **RAISED** BUMPED) MEETS OSHA 1910.212 **HEIGHT** ADJUSTABLE UPWARD TRAVEL LIMIT SWITCH-LOWERED **HEIGHT CORD EXITS FRAME** THIS END DIMENSION TOLERANCE ± 1/4" STANDARD FEATURES I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS MODEL NUMBER IS EHLT-4848-2-43-PSS REPRESENTED SATISFIES DESIGN AND DIMENSION PLATFORM WIDTH IS 48 3/8" REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION PLATFORM LENGTH IS 48 3/8" **OVERALL LENGTH IS 51"** PLATFORM RAISED HEIGHT IS 43" PLEASE CIRCLE SPECIFICATIONS COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE PLATFORM LOWERED HEIGHT IS 7"
TABLE CAPACITY (EVENLY DISTRIBUTED) AND LOCAL REGULATIONS AND STANDARDS **POWER** UNITS REQUIRING APPROVAL DRAWINGS OR 0 LOAD IS 2,000 LBS MODIFIED ARE NON-RETURNABLE INTERNAL POWER UNIT CONTROL IS HANDHELD, 2 BUTTON, NEMA 4 PENDANT WITH MINIMUM 8' USABLE COIL CORD MOTOR VOLTAGE 115 208 [] As drawn [] As marked DEDICATED CIRCUIT REQUIRED 60Hz Signed: SAFETY MAINTENANCE PROPS, DISPLACEMENT MOTOR PHASE SINGLE **THREE** STYLE CYLINDERS INSTALLED ROD DOWN **Printed Name: EMERGENCY SAFETY STOP HYDRAULIC FUSES** DISTRIBUTOR'S NAME: CONTROL **HAND** IN ALL CYLINDER, UNITS HAVE 2' TEST LEAD AND PIG TAIL DECK TOLERANCE ± 1/2" FRAME AND DECK - MILL FINISH 304 STAINLESS STEEL GREASABLE PINS AND ROLLERS - 17-4 STAINLESS STEEL TABLE HEIGHT TOLERANCE ± 1/2" VESTIL MANUFACTURING W.O.# SCISSOR LEGSET - CARBON STEEL WITH DECK FLATNESS ± 1/4" TOUGH BAKED IN POWDER COATED WHITE FINISH STAINLESS STEEL COMPONENTS HAVE AN UNPOLISHED (MILL) FINISH DATE: 8/30/2017 SALES: X SCALE: 1:12 FILE NAME: SPECIAL FEATURES Quoted lead time: $_{
m Y}$ QUOTE # 24-007-045-001 NONE