APPROX WEIGHT: 1120.96 lbs.

LIFT AND TILT SCISSOR TABLE - EHLTT-4848-1-47 ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE *** DOES NOT INCLUDE WEIGHT OF POWER OR PACKAGING!!! ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON CHAIN & HOOK STEEL CRADLE IS **(** 12" HIGH-48' SAFETY STOP (STOPS TABLE FROM DECK TOLERANCES +/- 1/2" OWERING IS BUMPED) TABLE HEIGHT TOLERANCES +/- 1/2" MEETS OSHA 1910.212 DECK FLATNESS +/- 1/4" OUF 56' 83 1/2" 47' 23 1/8" 1 1/8" HOSE & CORD EXIT 48" FRAME THIS END ADJUSTABLE UPWARD (4) ANCHORING LOCATIONS DIMENSION TOLERANCE ± 1/4" STANDARD FEATURES I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS REPRESENTED SATISFIES DESIGN AND DIMENSION PLEASE CIRCLE SPECIFICATIONS: MODEL NUMBER IS EHLTT-4848-1-47 Α REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO MAX CAPACITY IS 1.000 LBS POWFR Ρ AC CONFIRM PRODUCT AND INSTALLATION PLATFORM WIDTH IS 48" Ρ COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE FRAME WIDTH IS 30" MOTOR VOLTAGE 115 208 460 AND LOCAL REGULATIONS AND STANDARDS R **OVERALL LENGTH IS 56"** UNITS REQUIRING APPROVAL DRAWINGS OR DEDICATED CIRCUIT REQUIRED 60Hz 0 PLATFORM LENGTH IS 48" MODIFIED ARE NON-RETURNABLE ۷ MOTOR PHASE SINGLE THREE PLATFORM RAISED HEIGHT IS 47" [] As drawn [] As marked Α PLATFORM LOWERED HEIGHT IS 11" CONTROL FOOT HAND L Date: Signed: **OVERALL HEIGHT IS 83 1/2"** PLATFORM TILTS ON THE END OF THE LEG ASSEMBLY Printed Name: PLATFORM TILTING STYLE IS A SLIDE TILT LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING P.O.# X Ø1/4" x 60" CHAIN AND HOOK (NOT DRAWN TO SCALE) DISTRIBUTOR'S NAME: MAXIMUM TILT ANGLE IS 45° VESTIL MANUFACTURING W.O.# Х CONTROL IS HANDHELD, 4 BUTTON, NEMA 4 drawn by: BCN DATE: 2/3/2017 SALES: X PENDANT WITH MINIMUM 8' USABLE COIL CORD INTERNAL POWER UNIT REFERENCE: X SPECIAL FEATURES SCALE: 1:25 FILE NAME: DURABLE LIQUID PAINT BLUE FINISH NONE

QUOTED LEAD TIME: 🖌

QUOTE #

Х

02-007-021-001