APPROX WEIGHT: 158.73 lbs. **FORK EXTENSIONS - FE-6-84** DOES NOT INCLUDE WEIGHT OF POWER OR PACKAGING!! *** ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE *** ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON - 7 1/8" 8 3/8" 84" **USABLE LENGTH** 87 5/8" **OVFRAILLENGTH** FORK EXTENSION MATERIAL THICKNESS IS 5/16" 5/8" Ø 5/8" 2 5/16" CENTER OF GRAVITY 6 1/2" **USABLE WIDTH** SPECIAL FEATURES STANDARD FEATURES DIMENSION TOLERANCE ± 1/4" MODEL NUMBER: FE-6-84 I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS FORK EXTENSION WIDTH: 7 1/8" REPRESENTED SATISFIES DESIGN AND DIMENSION **OVERALL WIDTH W/LOOP: 8 3/8"** REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO Α **USABLE WIDTH: 6 1/2"** CONFIRM PRODUCT AND INSTALLATION Ρ **OVERALL LENGTH: 87 5/8"** COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE Ρ **USABLE LENGTH: 84"** AND LOCAL REGULATIONS AND STANDARDS. R FITS 6" WIDE x 2 1/2" MAX. THICKNESS FORK ANY MODIFIED UNITS ARE NON-RETURNABLE 0 SOLID STEEL CONSTRUCTION [] As drawn 1 As marked V TOUGH BAKED IN POWDER COATED YELLOW FINISH APPROX. WEIGHT / LOST LOAD = 158.73 LBS. PER PAIR Α Signed: Date: MINIMUM EFFECTIVE THICKNESS = LESS THAN 1 **Printed Name:** CAPACITY = 4,000 # PER PAIR, EVENLY DISTRIBUTED LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING FORK EXTENSIONS DO NOT CHANGE THE LOAD DISTRIBUTOR'S NAME: CENTER OF EXISTING FORK TRUCK. FOR INTERNAL USE ONLY NEVER EXCEED LOAD CENTER RATING PER FORK PROJECT SIGN OFF VESTIL MANUFACTURING W.O.# TRUCK MANUFACTURER'S GUIDELINES. **SALES** DO NOT USE THESE FORK EXTENSIONS IF LOAD WILL PATE: 9/1<u>9/06</u> SALES: X Q.WESTFALL ENG. EXCEED FORK TRUCK MANUFACTURER'S LOAD reference: X SCALE: 1:14 FILE NAME: CENTER RATING. FAB. FORK EXTENSIONS MUST NOT EXCEED 150% QUOTED LEAD TIME: $_{ m Y}$ 08-007-094 QUOTE # POWER ORIGINAL FORK LENGTH. Χ