LIFT MASTER BOOM, LIFT MASTER ONE, TELESCOPING BOOM - LM-1T-4-24 APPROX WEIGHT: 434.28 lbs. \*\*\* ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE \*\*\* ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON 151 1/4" 24" FORK ■ POCKET -> **CENTERS** 25 7/8" 13 3/16" **VERTICAL CENTER OF GRAVITY** 

## \*--MAXIMUM SINGLE HOOK CAPACITIES

DISTANCE	36"	48"	60''	72"	84"	96"	108"	120"	132"	144"
CAPACITY	4000	3750	3500	3250	3000	2750	2500	2250	2000	1750

## STANDARD FEATURES

MODEL NUMBER: LM-1T-4-24 CAPACITY: 4,000 LBS LOST LOAD - 435 LBS OVERALL HEIGHT - 25 7/8" LENGTH (RETRACTED) - 86" LENGTH (EXTENDED) - 151 1/4" OVERALL' WIDTH - 32" USABLE FORK POCKET - 2 1/2" X 7 1/2 24" FORK POCKET CENTERS 36" MINIMUM HOOK POINT 144" MAXIMUM HOOK POINT **EFFECTIVE THICKNESS: LESS THAN 1"** TOUGH BAKED IN POWDER COATED BLUE BASE FRAME

W/ YELLOW EXTENSION NEVER EXCEED LOAD CENTER RATING PER FORK TRUCK MANUFACTURER'S GUIDELINES. DO NOT USE THIS FORK TRUCK ATTACHEMENT IF LOAD WILL EXCEED FORK TRUCK MANUFACTURER'S LOAD CENTER RATING.

## SPECIAL FEATURES NONE

**POWER** 

Ρ Ρ R 0

V

Α

QUOTED LEAD TIME: X

32 11/16" RETRACTED **CENTER OF GRAVITY** 

48 3/4" EXTENDED CENTER OF GRAVITY

## **DIMENSION TOLERANCE ± 1/4"**

I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS REPRESENTED SATISFIES DESIGN AND DIMENSION REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS AND STANDARDS. ANY MODIFIED UNITS ARE NON-RETURNABLE [ ] As drawn [ ] As marked Signed: Date: **Printed Name:** TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING

	LEAD TIME
OR INTERNAL USE ONLY	DISTRIBUTOR'S NAME
PROJECT SIGN OFF	VESTIL M
SALES	
ENG.	DRAWN BY: BCN
ΕΛR	REFERENCE: X

. MANUFACTURING

QUOTE #

16" HORIZONTAL **CENTER OF GRAVITY** 

> W.O.# X SALES: X 6/1/2016 SCALE: 1:22 FILE NAME:

> > 08-007-128