

34 5/8" RETRACTED **CENTER OF GRAVITY**

52 7/8" EXTENDED

CENTER OF GRAVITY

*MAXIMUM SINGLE HOOK CAPACITIES											CENTER OF GRAVITY	
DISTANCE	36"	48"	60''	72"	84"	96"	108"	120"	132"	144"		
CAPACITY	4000	3750	3500	3250	3000	2750	2500	2250	2000	1750		

STANDARD FEATURES

13"

MODEL NUMBER: LM-EBT-4-36 CAPACITY: 4,000 LBS LOST LOAD - 385 LBS OVERALL HEIGHT - 13 3/16" LENGTH (RETRACTED) - 86 1/4" LENGTH (EXTENDED) - 151 1/2" OVERALL WIDTH - 44" USABLE FORK POCKET -2 1/2" X 7 1/2" 36" FORK POCKET CENTERS 36" MINIMUM HOOK POINT 144" MAXIMUM HOOK POINT EFFECTIVE THICKNESS: LESS THAN 1" TOUGH BAKED IN POWDER COATED

BLUE BASE FRAME W/ YELLOW EXTENSION

NEVER EXCEED LOAD CENTER RATING PER FORK TRUCK MANUFACTURER'S GUIDELINES. DO NOT USE THIS FORK TRUCK ATTACHEMENT IF LOAD WILL EXCEED FORK TRUCK MANUFACTURER'S LOAD CENTER RATING.

SPECIAL FEATURES NONE

REPRESENTED SATISFIES DESIGN AND DIMENSION REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO Α CONFIRM PRODUCT AND INSTALLATION P COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE Ρ R 0 [] As drawn l As marked V Α Signed:

DISTRIBUTOR'S NAME:

REFERENCE:

AND LOCAL REGULATIONS AND STANDARDS. ANY MODIFIED UNITS ARE NON-RETURNABLE

7 1/2

DIMENSION TOLERANCE ± 1/4" I. THE UNDERSIGNED, AGREE THAT THE PRODUCT AS

Printed Name:

LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING

13 3/16"

22" HORIZONTAL

VESTIL MANUFACTURING

B.NOTHNAGEL

W.O.# X SALES: X 6/16/2015 SCALE: 1:25 FILE NAME:

Date:

FAB. **POWFR**

SALES

ENG.

FOR INTERNAL USE ONLY

PROJECT SIGN OFF

QUOTED LEAD TIME: $_{
m Y}$

QUOTE # Χ

08-007-197