





3D VIEW FOR REFERENCE ONLY

PLEASE CIRCLE SPECIFICATIONS:

	POWER	AC		DC	(12V) AIR/	OIL			
	MOTOR V	OLTAGE		115	208	230	460			
	DEDICATED CIRCUIT REQUIRED									
	MOTOR PHASE			INGL	E -	THREE				
*	CONTROL		* HAND			FOOT				
	~ ALL BATTERY CHARGERS ARE 115V AC ~									
*	BATTERY CH	IRG.		MOT		ON-BC				

* AVAILABLE AT ADDITIONAL COST

STANDARD FEATURES

MODEL NUMBER IS VAN-J-AC CAPACITY IS 400 LBS.
OVERALL WIDTH IS 9 15/16"
USABLE WIDTH IS 8"
OVERALL LENGTH IS 45 3/4"
USABLE LENGTH IS 39 3/4"
OVERALL HEIGHT IS 46 1/16"
USABLE HEIGHT IS 42 1/8"
HOLES ON BASE ARE Ø7/8" X 1 1/4" SLOTS ROTATES 360° AROUND BASE INCLUDES AC POWERED WINCH WITH FINGER TOGGLE SWITCH Ø7/32" X 25' LG CABLE W/ HOOK

SPECIAL FEATURES

NONE

A P P R O	REF REQU COM A	UNDERSIGNED, AGREE THAT THE PRODUCT AS RESENTED SATISFIES DESIGN AND DIMENSION REMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION PLIANCE WITH ALL APPLICABLE FEDERAL, STATE ND LOCAL REGULATIONS AND STANDARDS. SPECIAL UNITS ARE NON-RETURNABLE [] As drawn [] As marked				
Ă	Signed:	Date:	_			
L		LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING				
ISTRI	BLITOR'S NAA	F· P O #	_			

OF GIGHTED AND THE BIOWING								
DISTRIBUTOR'S NAME:	P.O.# X							
VESTIL MANUFAC	W.O.# X							
DRAWN BY: ND	DATE: 11		SALES: X					
reference: X		SCALE: 1:11						
QUOTED LEAD TIME: X	QUOTE #	Χ	28-007-283					