

# MARTO



## 804-87046

### Sizes

UK 6-13

### Range

IWS Exclusive

### Colour

Wheat

### Description

Premium 6" zip sided lace-up safety boot.



### BOOT DETAILS












<b>Industry</b>	Civil Mining Construction
<b>Construction</b>	Cement
<b>Upper Material</b>	Nubuck Leather
<b>Lining Material</b>	Comfort Mesh
<b>Insole</b>	Polyurethane
<b>Safety Toe Cap</b>	Steel
<b>Midsole</b>	Polyurethane
<b>Outsole</b>	Rubber

### STANDARD CERTIFICATION

- AS 2210.3:2019 SB FO SRC
- ASTM F2413-18 EH Resistant



### BOOT FEATURES

- 
**Padded Collar & Tongue**  
 Added foam around the ankle & shin area to provide better support, stability and comfort.
- 
**Wheat Nubuck Leather Upper**  
 Made from high quality, long lasting nubuck leather.
- 
**Steel Toe Cap**  
 Capable of resisting a drop force of 200 joules to offer premium protection for your toes.
- 
**Toe Scuff Protection**  
 Added toe scuff and abrasion protection to prolong the life of the boot.
- 
**C.T.S PU Footbed**  
 For increased underfoot cushioning performance. Designed to mould and support the foot with added arch support.
- 
**EH Protection**  
 Minimises the flow electricity to the ground, reducing the risk of electrocution.
- 
**Comfort Mesh Lining**  
 Premium comfort lining provides soft and breathable boot interior to keep your feet dry and cool.
- 
**YKK Zipper**  
 High quality zipper provides a quick release and ease of access.
- 
**C.T.S High Rebound Midsole**  
 Specifically formulated high energy PU compound, designed to absorb shock and return energy.
- 
**Slip, Fuel & Oil Resistant**  
 Designed to meet the slip, fuel & oil resistance for standard AS/NZS 2210.3:2019 FO SRC
- 
**C.T.S Rubber Outsole**  
 Hardwearing C.T.S Rubber Outsole for superior durability and grip.