
## **Foot & Check Valves**



#### **APPLICATION**

ANKA Foot Valves are a spring-loaded non-return valve with a screen which are used at the suction end of pump lines to prevent loss of water and pump prime.

ANKA Check Valves are a spring-loaded non-return valve which can be used in a variety of cold water applications including irrigation, plumbing, marine, domestic, agricultural and industry to allow water to flow in one direction only.



- Install at any angle
- Durable, versatile and non-corrodible materials
- Can be taken apart for cleaning
- Does not restrict flow
- Spring-loaded

#### **HOW IT WORKS**

- Plunger opens fully when pump turns on
- Water flows through valve
- Plunger securely closes & seals

#### **SPECIFICATIONS**

Working Pressure: 1600kpa (230psi) @ 20°C (68°F) **Temperature Range:** Cold water applications

Threads: BSPT

Materials: Glass Fibre Reinforced Nylon body

316 Stainless Steel spring

Acetyl plunger


Nitrile rubber washer & o-rings

Polypropylene screen (Foot Valves only)





**Check Valves** 



# Foot & Check Valves



#### **AVAILABLE SIZES**



#### Foot Valve

- 15mm (½")
- 20mm (¾")
- 25mm (1")
- 32mm (11/4")
- 40mm (1½")
- 50mm (2")




#### Check Valve

- 15 x 15mm (½" x ½")
- 15 x 15mm (1/2" x 1/2") Male x Female
- 20 x 20mm (¾" x ¾")
- 25 x 25mm (1" x 1")
- 32 x 32mm (1 1/4" x 11/4")
- 40 x 40mm (1 ½" x 1½")
- 50 x 50mm (2" x 2")

#### **SPARES & ACCESSORIES**

Spare screens



### Performance Curve (Foot & Check Valves)

