



The pump is a submersible drainage pump fitted with semi vortex, urethane coated impeller plus agitator, supplied wired and ready to install. The pump has a dual mechanical seal in oil chamber and can handle particles to 25 mm x 10mm.

**The pump is characterised by:**

- Corrosion resistant pump components.
- Fully automatic operation.
- Dual Mechanical Seal in oil bath, SIC/SIC, Carbon Ceramic.
- Urethane coated semi vortex impeller allows pumping of suspended solids, sandy and stringy material.
- Agitator on the end of the pump shaft helps prevent airlocking and clogging.
- Carry handle.
- Versatile outlet connection.
- 240V single phase motor with in-built auto reset thermal overload.
- Suitable for construction sites, storm water, basements.

**Liquid:**

Clean water temperature range: 2 – 35 °C

**Materials:**

Pump body: Cast Iron  
 Strainer: Urethane  
 Impeller: Urethane coated semi vortex  
 Shaft: Stainless Steel 403  
 Shaft seal: Dual Mechanical in oil bath, Silicon Carbide/Silicon Carbide + Carbon/Ceramic

**Installation:**

Maximum ambient temperature: 40 °C  
 Maximum submergence: 8m  
 Pipe connections discharge: 2"

CLA-BLUESUB10	10A
Max Flow: (l/m)	250
Max Head: (m)	18
Rated voltage: (V)	240
Mains frequency: (Hz)	50
Rated output: (W)	750
Current: (amps)	5.6
Capacitor: (uF)	25
Motor duty:	Continuous
Motor type:	Asynchronous
Motor protection:	In-built thermal overload
Ingress protection:	IP 68
Insulation class:	B
Power cable length:	10m H07RNF
Net weight: (kg)	19.2
Dimensions: LxHxW (mm)	320x430x225

**12 Month Claytech Warranty**

**Also available**

BIA-LAYFLATKIT Lay Flat Hose 20m, 2"