

Description	Value
General information:	
Product name:	CMBE 3-62 I-U-C-A-D-A
Product No:	98374709
EAN number:	5711493909491
Price:	
Technical:	
Pump speed on which pump data are based:	3780 rpm
Rated flow:	4.2 m ³ /h
Rated head:	45.2 m
Impellers:	4
Primary shaft seal:	AVBE
Approvals and markings:	CE
Curve tolerance:	ISO9906:2012 3B
Model:	A
Return valve:	YES
Start pressure:	Integrated Frequency converter
Materials:	
Pump housing:	Stainless steel
Pump housing:	DIN W.-Nr. 1.4301
Pump housing:	AISI 304
Impeller:	Stainless steel
Impeller:	DIN W.-Nr. 1.4301
Impeller:	AISI 304
Rubber:	EPDM
Installation:	
t max amb:	55 °C
Flange standard:	WHITWORTH THREAD RP
Pump inlet:	Rp 1
Pump outlet:	Rp 1
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	0 .. 60 °C
Selected liquid temperature:	20 °C
Density:	998.2 kg/m ³
Electrical data:	
Rated power - P2:	1.1 kW
Mains frequency:	50 / 60 Hz
Rated voltage:	1 x 200-240 V
Maximum current consumption:	6.70-5.60 A
p max system:	10 bar
Rated speed:	360-4000 rpm
Enclosure class (IEC 34-5):	IP55
Insulation class (IEC 85):	F
Type of cable plug:	AU
Mains cable:	1.5 m
Tank:	
Tank volume:	2 l
Others:	
Net weight:	17 kg
Gross weight:	27.1 kg
Sales region:	Australia
Config. file no:	98390434
Country of origin:	CN
Custom tariff no.:	8413709062

