

MINI-CLITM

This sensor halts scheduled irrigation when it detects a preset level of rain has fallen to stop water waste.

KEY BENEFITS

- Shuts off irrigation automatically when the sensor detects rainfall from 3 mm to 19 mm
- Debris tolerant for reliable operation and no unnecessary shutdowns
- Compatible with most normally open or normally closed irrigation controllers

OPERATING SPECIFICATIONS

- Switch rating (24 VAC): 3 A
- Includes 7 m of 0.5 mm² sheathed, UL-approved wire
- Approvals: UL, cUL, FCC, CE, RCM
- Warranty period: 5 years

USER-INSTALLED OPTIONS

- Optional Gutter Mount (P/N SGM)

Sensor: **Rain, Freeze**



Mini-Clik Sensor
(with mounting arm)
Height: 5 cm
Length: 15 cm
Width: 2.5 cm



Mini-Clik Sensor
(with stainless steel enclosure)
Height: 13.9 cm
Length: 7.6 cm
Width: 10.1 cm

SENSORS

MINI-CLI TM	
Model	Description
MINI-CLI TM	Mini-Clik Sensor
MINI-CLI TM -NO	Mini-Clik Sensor, normally open switch
MINI-CLI TM -C	Mini-Clik Sensor, conduit mount
SG-MC	Mini-Clik Sensor in a stainless steel sensor enclosure

Compatible with:



Waterproof Wire Connector