

EDGE IP Analog 8™

Broadcast Quality Multichannel IP Decoder with IP Input and Analog Video and Audio Outputs. Output is up to 8 Composite Standard Definition Analog Outputs from Standard Definition MPEG-2, H.264/MPEG-4 or AVC Inputs. Audio Output is Unbalanced Audio, 8 Stereo Pairs. Optional Balanced Audio with XLR Connectors. Set Up via LCD Front Panel or via Browser.



Features

- Inputs: IP (100/1000 M)
- Outputs: Up to eight channels of standard definition analog (CVBS) video
- Audio Outputs: Composite unbalanced audio – up to eight stereo pairs
- Decodes to multiple MPEG-2 or MPEG-4 AVC streams
- Highly reliable hardware and software design
- Multiple protective mechanisms such as power failure memory recovery, over-voltage, over-load, short-circuit protection
- Supports PAL and NTSC
- LCD front panel controls plus web-based management
- Supports remote software upgrades

Applications

- MPEG-2/4/H.264 SD Decoder
- Content repurposing
- Multichannel IP decoder

Overview

The EDGE IP Analog 8 is a broadcast quality multi-channel IP decoder. It is unique in that it can decode up to eight unscrambled SD MPEG-2 or H.264/MPEG-4 AVC streams to "old fashioned" analog.

The system supports a wide range of input and output options: IP, and optionally DVB-S/S2 or DVB-ASI; allowing it to handle any program sources. It decodes to analog composite video (CVBS) and unbalanced or balanced audio interfaces.

The EDGE IP Analog 8 can decode up to eight SPTS IP inputs in one rack unit. It features a web-based setup for local and remote management and maintenance, which significantly reduces management time and operating expenses (OPEX) for operators.



Computer Modules, Inc.
11409 West Bernardo Court
San Diego, CA 92127
Tel: 858-613-1818 Fax: 858-613-1815
www.dveo.com

Rear View



Specifications

IP Input

Protocol:	UDP
Type:	Multicast, Unicast (IGMPv1, IGMPv2)
Effective Bit Rate:	≤800 mbps
Ethernet Connector:	100/1000 M Base-T, Full Duplex, RJ45

Optional DVB-ASI Input

Inputs:	One input, one loopthrough input
Connectors:	One BNC female, 75 ohm
Bytes per packet	188
Bitrate:	≤100 mbps

Video Decoding

Decoding Profile and Level:	MPEG-2 SD MP@ML MPEG-4 AVC SD MP@ML AVS
Resolutions and Frame Rates:	PAL: 576i @ 25 fps NTSC: 480i @ 30 fps
Aspect Ratio:	4:3

Audio Decoding

Format:	MPEG-1 Layer II, MPEG-2
Operation Mode:	Stereo or Mono
Sample Rates:	32 KHz, 44.1 KHz, 48 KHz
Audio Bitrate:	192-384 kbps

Audio Video and Audio Output

Composite Video:	8x CVBS, BNC Female 75Ω
Unbalanced Audio:	8x Stereo Pairs (R/L), BNC Female 600Ω
Operation Modes:	Stereo or Mono mode

Optional Analog Balanced Audio (2 RU Unit)

Numbers of Interface:	8x CVBS, BNC Female 75Ω
Connector Type:	8x Stereo Pairs (R/L), BNC Female 600Ω
Operation Modes:	Stereo or Mono mode

Control & Monitoring

Front Panel Controls:	Front panel operation, LCD display LED indicator light
6 Keys:	Up, Down, Left, Right, Enter, ESC
Remote:	100M Base-T Ethernet, RJ45, Web (IE 8.0 or above)

Physical & Power

Rated Voltage:	AC 110-240V 50/60Hz
Rated Power:	30W
Operating Temperature:	-10~50°C (-10~122°F)
Storage Temperature:	-10~75°C (-10~167°F)
Dimensions – LxWxH:	1 RU: 17.72 x 19 x 1.75 inches (450 x 483 x 44.5 mm) 2 RU: 17.72 x 19 x 3.5 inches (450 x 483 x 89 mm)
Weight:	1 RU: 3 Kg 2 RU: 6 Kg
Conformities:	FCC, CE, RoHs

Ordering Info

EDGE IP Analog 8
 EDGE IP Analog 8 with Optional DVB-S/S2 input
 EDGE IP Analog 8 with Optional DVB-ASI input
 EDGE IP Analog 8 with Optional Balanced Audio



Computer Modules, Inc.
 11409 West Bernardo Court
 San Diego, CA 92127
 Tel: 858-613-1818 Fax: 858-613-1815
www.dveo.com