PRO-HD SERIES

FIREWOOD PROCESSORS





TIMBERWOLF

FIREWOOD PROCESSING EQUIPMENT



607-307-4029

www.TimberwolfEquip.com



- Rugged frame for maximum durability
- ▲ All processors are capable of splitting a minimum of 2.5 cords per hour and as many as 4 full cords per hour
- ▲ State-of-the-art hydraulics make these processors the most efficient on the market at this price point




FEATURES



Power

- · Choose 4" or 5" bore
- 3-Stage Gear Pump
- 70 gallon Hydraulic Tank



Clamping System

- Patented Top Roll Clamping System applies up to 1000 lbs of force down on the log to ensure stability
- Large toothed Back Roller enhances traction so longer logs are fed forward



Live Deck

- Full 8' in length allows up to one full cord to be stored and handled
- Roller chain allows deck to move heaviest logs with ease
- Stores vertically for easy transport



Integrated Conveyor

- 12' long with a 10'10" maximum loading height
- · 20" wide paddle belt
- Fully reversible for simple set up and attachment

All Pro-HD Series Processors come standard with a 4-Way Wedge and 3 Strand Live Deck. 5 Strand Live Deck and Integrated Conveyor are available as Add-On Options.

SPECIFICATIONS

Base Model	Pro-HD	Pro-HD X	Pro-HD XL
Engine Power (HP)	56	56	74
Pump Flow (GPM)	22-22-18	22-22-18	33-18-14
Stroke (in.)	26	26	26
Trough Length (ft)	16	16	16
Max Log Length (ft)	32	32	32
Cycle Time (sec)	5.9/9.1	4.1/6.1	3/4.5
Average Output (Cord/Hr)	2.5	3	4
Dimensions (H"xW"xL")	129"x195"x409"	129"x195"x409"	129"x195"x409"
Weight (lbs)	9,200	9,200	9,200

