## TWC SERIES

**CONVEYORS** 





# TIMBERWOLF

FIREWOOD PROCESSING EQUIPMENT



607-307-4029 www.TimberwolfEquip.com



- ▲ Our customers often recommend investing in a conveyor prior to upgrading their log splitters as they have an incredible ability to boost production and profit
- ▲ All TWC conveyors can be transported in tow and have at least 3' of vertical range
- All conveyors have tapered rollers for self-adjusting belt tracking
- ▲ Increase in your productivity for as little as \$4,500



## **FEATURES**



#### **Telescopic Axles**

- Hydraulic lift cylinder powered by tandem center spool valve
- Provides excellent mobility and stability while in operation



#### **Ground Skid**

- Provides additional stability by anchoring to solid ground
- Lifts the roller off the ground, allowing more room for debris to fall



#### **Modular Hopper**

- Heavy-duty, bolt-on design
- Funnel-like shape makes loading logs simple
- Easily pairs with any Timberwolf log splitter



#### Belt

- Choose paddle belt or rough top belt, both are 20" wide
- Rubber belt fines deflector prevents debris from falling into roller
- Self-aligning tapered rollers for correct belt tracking

The TWC-16, TWC-24, and TWC-32 Conveyors are available with optional Grizzly Bars.

### **SPECIFICATIONS & DIMENSIONS**

| Base Model        | TWC-12 | TWC-16 | TWC-24 | TWC-32 |
|-------------------|--------|--------|--------|--------|
| Engine Power (HP) | 4.9    | 4.9    | 4.9    | 4.9    |
| Travel Height     | 5′3″   | 7′     | 8′     | 8′     |
| Min Height        | 5′5″   | 7′9″   | 7′8″   | 7′5″   |
| Max Height        | 8′     | 10′    | 13′2″  | 14′1″  |
| Max Angle         | 29     | 29     | 29     | 29     |
| Frame Width       | 1′10″  | 1′10″  | 1′10″  | 1′10″  |
| Weight (lbs)      | 1,055  | 1,200  | 1,730  | 2,040  |



