

# IDEALSEAL FIRECHECK INTUMESCENT SEALANT CE DECLARATION OF PERFORMANCE



DECLARATION OF PERFORMANCE in accordance with Annex III of Regulation (EU) No 305/2011 (Construction Product Regulation)

### DoP \_ [EN] \_ 001 \_ No IS510018

1. Unique identification code of product-type:

## **IDEALSEAL FIRECHECK INTUMESCENT SEALANT**

2. Type, batch or serial number or any other element allowing identification of the construction product as required to Article 11 (4):

# Batch number: See product packaging

3. Intended use or uses of construction product, in accordance with applicable harmonized technical specification, as foreseen by the manufacturer:

#### Sealants for façade elements EN 15651-1: F-EXT-INT (CLASS 7.5P)

4. Name, registered name or registered trade mark and contact address for the manufacture as required to Article 11 (5):

### IDEAL SEALANTS LTD, UNIT D5 TAYLOR BUSINESS PARK, RISLEY, WARRINGTON, WA3 6BL

- 5. Name and contact address of the authorized representative whose mandate covers the task specified in Article 12 (2): not relevant
- 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

# System 3 System 3 for reaction to fire

7. In case of declaration of performance concerning a construction product covered by a harmonized standard:

The notified body SKZ – TeConA GmbH (1213) performed the initial type testing according to EN 15651-1 and reaction to fire under system 3 and issued a: test report.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: not relevant



# IDEALSEAL FIRECHECK INTUMESCENT SEALANT CE DECLARATION OF PERFORMANCE

9. Declared performance:

Conditioning Procedure A (according to ISO 8340) Mortar M2 (with primer MSP)

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Class E	
Release of chemicals dangerous to the environment and health	NPD (*)	EN 15651-1:2012
Water tightness and air tightness		E14 15051-1.2012
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 25 %	
Tensile properties after immersion in water (at 23°C)	≥ 25 %	
Durability	Pass	

(\*) See material safety data sheet NPD: No Performance

Determined

Where pursuant in Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not relevant

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Matthew Kenny Company Director Ideal Sealants Ltd 15/10/2022