



### DECLARATION OF PERFORMANCE

**DoP \_ [EN] \_ UK1 \_ No UKIS510018**

1. Unique identification code of product-type:

**IDEALSEAL FIRECHECK INTUMESCENT SEALANT**

2. Intended use or uses of construction product, in accordance with applicable harmonized technical specification, as foreseen by the manufacturer:

**Sealants for façade elements  
EN 15651-1:2012 : F-EXT-INT (CLASS 7.5P)**

3. Name, registered name or registered trade mark and contact address for the manufacture as required to Article 11 (5):

**IDEAL SEALANTS LTD, UNIT D5 TAYLOR BUSINESS PARK, RISLEY, WARRINGTON, WA3 6BL**

4. System or systems of assessment and verification of constancy of performance:

**System 3**

5. Designated Standards

**EN 15651-1**

6. Approved Body

**2538, 4ward Testing Ltd**



7. Declared performance:  
Conditioning Procedure A  
: Substrate: Mortar 2

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire (EN ISO 11925-2:2020)	<b>Class E</b>	<b>EN 15651-1:2012</b>
Release of chemicals dangerous to the environment and health	<b>NPD (*)</b>	
<b>Water tightness and air tightness</b>		
Resistance to flow (EN ISO 7390)	<b>≤ 3 mm</b>	
Loss of volume (EN ISO 10563)	<b>≤ 25 %</b>	
Tensile properties after water immersion (EN ISO 10591)	<b>≥ 25%</b>	
<b>Durability</b>	<b>Pass</b>	

(\*) See material safety data sheet  
NPD: No Performance Determined

8. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Matthew Kenny  
Company Director  
Ideal Sealants Ltd  
15/10/2022