



Idealseal MS290 MS Polymer (Clear)

The ultimate crystal clear all in one anti-pick sealant and adhesive for wet or dry applications even cures underwater.



Description

Idealseal MS290 is the ultimate all-round sealant and adhesive offering a durable, flexible, environmentally friendly alternative to traditional sealants, adhesives and putty. It is odourless, non-toxic, low V.O.C., free of isocyanates, solvents and silicones. MS290 has excellent adhesion to dry and wet surfaces without the risk of shrinkage or bubbling and will even cure underwater. Once cured it is paintable and resistant to chemical, fungal and bacterial attack. Tested to EN1186, EN13130, CEN/TS 14234 and approved for use in food preparation areas. Also tested and approved for use on self-cleaning glass.

Uses

Idealseal MS290 is suitable for virtually any application where a sealant, adhesive or filler is required. It will seal and bond; wood, glass, ceramics, concrete, metals including lead, fibreglass, EPDM, butyl rubber, vinyl and most plastics.

Common applications include automotive, bathroom and wet room, caravan and mobile home, marine, pond and general construction. MS290 is also suitable for use in correctional institutions and areas where vandalism of sealant may occur due to its excellent anti-pick qualities. Furthermore, it can be used safely in cleanrooms and cold storage.

Technical Detail

Base		MS Polymer
100% Modulus	DIN 53504 S2	1.15 N/mm ²
Application rate	@ Ø2.5mm/ 6.3 bar	150-300g/min
Application temperature		+ 5°C to +40°C
Curing time	@ +23°C/50% RH	2-3mm/24 hours
Density	ISO 1183-1	1.06g/ml
Elongation at break	DIN 53504 S2	450%
Frost resistance during transportation		Up to -15°C
Joint movement		25%
Shorea hardness	DIN 53505	45
Skin formation	DBTM 16	10 minutes @ +23°C/50%RH
Temperature resistance		- 40°C to +90°C
Tensile strength	DIN 53504 S2	3.20 N/mm ²

Colour

Clear

Packaging

290ml x 12

Application

Surfaces must be algae, grease, and dust free. Ensure temperature is above 5°C (for underwater applications ensure water temperature is above 5°C).

Cut the cartridge seal and screw on nozzle which should be cut to required size. Gun the sealant firmly into joint ensuring no air is trapped behind. If required place masking tape along joint edges, removing within 5 minutes of application.

Limitations

Due to the large diversity of surfaces a compatibility and adhesion test is advisable prior to application.



Paintability

This product is paintable with most water based and two component paints. A compatibility test before application is recommended. Not paintable with alkyd resin paints.

Shelf Life

In unopened original packaging between + 5°C and +25°C, shelf life up to 24 months from production date stated on the tube, store in a dry place

Certifications

	EN 15651-1: F-INT
	ISEGA- Certification for use in food preparation areas
	A+ French VOC Regulation LEED

Health and Safety

Safety data sheet (MSDS) must be read and understood before use of the product this is available on request and via www.ideal Sealants.com.

Liability

The information given is the result of our tests and experience and is believed to be accurate and reliable. However as Ideal Sealants Limited cannot know all the uses its products may be put to, and as application methods are out of our control it is the user's responsibility to determine suitability of use.

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Ideal Sealants Ltd. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Ideal Sealants Ltd written consent. The technical information in this document serves as an indication and is non-exhaustive. Ideal Sealants Ltd is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Ideal Sealants Ltd reserves the right to amend the wording of this document. Ideal Sealants Ltd cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever.