

Idealseal PU Gun Foam

A premium grade, easy to use, gun applied expanding foam for filling, fixing, insulating and backing.



Description

Idealseal PU Gun Foam is a high specification, multi-use, polyurethane based expanding foam. It has been formulated to combine high insulation, thermal and acoustic value with very good adhesion to the majority of surfaces

Uses

Idealseal PU Gun Foam is suitable for filling, fixing, insulating and backing applications in the general construction industry. Applications include: filling large irregular or awkward gaps; fixing window frames, loose tiles and boards; insulating between brickwork and cladding, around ductwork and through cavities carrying pipes and cables; and as a backing material in all types of sealant applications. Idealseal PU Gun Foam is compatible with wood, brick, concrete, masonry, metal and most plastics.

Technical Detail

Base		Polyurethane
Application temperature		+ 5°C to +35°C
Closed cells		± 70%
Curing time		80-100 minutes
Cutting time	EN 17333-3	20-40 minutes
Density		18-25 kg/m ³
Dimensional stability	EN 17333-2	-5% < DS < 0%
Fire behaviour	DIN 4102-1	B3
Joint sound insulation		62 dB
Tack free time	EN 17333-3	8-12 minutes
Temperature resistance		- 40°C to +90°C
Thermal conductivity		30-35 Mw/m.K
Total foam yield	EN17333-1	750 ml = 42-48 litres

Colour

Green

Packaging

750ml x 12

Application

Surfaces must be clean and dust, grease and oil free. It is important to moisten surfaces slightly before use to improve adhesion and finished cell structure of the foam.

Remove cap, hold can upright and fix on to applicator gun. Shake the can intensively at least 30 times prior to use. To apply foam, turn the can upside down.

Filling: Half fill the cavity and lightly spray the foam with water. The foam will expand to fill the rest.

Fixing: When fixing window frames use wedges to hold the frame in place until the foam is fully cured - approximately 24 hours.

Limitations

Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous surfaces. Not suitable for permanent water load.

Paintability

Can be painted or covered with sealant/plaster when fully cured.

Cleaning

Fresh foam can be removed immediately with PU Foam Cleaner. After curing surplus foam can be removed with a knife or spatula and foam surface can be finished

Shelf Life

If kept in unopened original packaging between +5°C and +25°C and stored in a dry place, shelf life up to 24 months from production date stated on the can. Store the canisters in an upright position.

Certifications

ISO 717-1 Joint Sound Insulation Feica TM1011 Compression Strength Feica TM1012 Shear Strength Feica TM1018 Tensile Strength EN 1609 Water vapour partial immersion EN 12086 Water vapour transmission EN 12667 Thermal Performance DIN 12354-3 Joint Sound Insulation VOC emissions ISO 16000 EMICODE EC1 Plus – very low emission
--

Health and Safety

Safety data sheet (MSDS) must be read and understood before use of the product this is available on request and via www.idealsealants.com.

Liability

The information given is the result of our tests and experience and is believed to be accurate and reliable. However as Ideal Sealants Limited cannot know all the uses its products may be put to, and as application methods are out of our control it is the user's responsibility to determine suitability of use.

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Ideal Sealants Ltd. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Ideal Sealants Ltd written consent. The technical information in this document serves as an indication and is non-exhaustive. Ideal Sealants Ltd is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Ideal Sealants Ltd reserves the right to amend the wording of this document. Ideal Sealants Ltd cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever.