

BOSTIK FP404 FIRE RET PU GUNFOAM
 Supersedes Date: 07-Sep-2018

Revision Date 04-Jun-2019
 Revision Number 2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product Name BOSTIK FP404 FIRE RET PU GUNFOAM
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Aerosol.
Uses advised against Consumer use.

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik BV
 De Voerman 8
 PO Box 303
 5215 MH's-Hertogenbosch, The Netherlands
 Tel: +31 736 244 244
 Fax: +31 736 244 344

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Emergency Telephone No information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Acute toxicity - Oral	Category 4 - (H302)
Acute toxicity - Inhalation (Dusts/Mists)	Category 4 - (H332)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Respiratory sensitisation	Category 1 - (H334)
Skin sensitisation	Category 1 - (H317)
Carcinogenicity	Category 2 - (H351)
Specific target organ toxicity (single exposure)	Category 3 - (H335)
Specific target organ toxicity (repeated exposure)	Category 2 - (H373)
Aerosols	Category 1 - (H222, H229)

2.2. Label Elements

Contains: 2,2-dimethylpropan-1-ol, tribromo derivative, 2-Propanol, 1-chloro-, phosphate (3:1), Isocyanic acid, polymethylenepolyphenylene ester

Safety Data Sheet

BOSTIK FP404 FIRE RET PU GUNFOAM
Supersedes Date: 07-Sep-2018

Revision Date 04-Jun-2019
Revision Number 2



Signal word
DANGER

Hazard statements

H302 - Harmful if swallowed
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335 - May cause respiratory irritation
H351 - Suspected of causing cancer
H373 - May cause damage to organs through prolonged or repeated exposure
H222 - Extremely flammable aerosol
H229 - Pressurised container: May burst if heated

EU Specific Hazard Statements

EUH204 - Contains isocyanates. May produce an allergic reaction

Precautionary statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P211 - Do not spray on an open flame or other ignition source
P251 - Do not pierce or burn, even after use
P260 - Do not breathe spray
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P342 + P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor
P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Additional information

This product requires tactile warnings if supplied to the general public. .

Reserved for industrial and professional use.

2.3. Other Hazards

In case of insufficient ventilation and/or through use, the formation of a explosive/highly flammable mixture is possible

PBT and vPvB assessment

This preparation contains no substance considered to be persistent, bio-accumulating nor toxic (PBT)

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No.	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
---------------	--------	---------	----------	---	------------------------------------	---------------------------

Safety Data Sheet

BOSTIK FP404 FIRE RET PU GUNFOAM
Supersedes Date: 07-Sep-2018

Revision Date 04-Jun-2019
Revision Number 2

Isocyanic acid, polymethylenepolyphenylene ester	618-498-9	9016-87-9	40 - <80	STOT SE 3 (H335) STOT RE 2 (H373) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Resp. Sens. 1 (H334) Skin Sens. 1 (H317) Carc. 2 (H351) Acute Tox. 4 (H332)	STOT SE 3 :: C>=5% Skin Irrit. 2 :: C>=5% Eye Irrit. 2 :: C>=5% Resp. Sens. 1 :: C>=0.1%	Exempt(P)
2-Propanol, 1-chloro-, phosphate (3:1)	237-158-7	13674-84-5	20 - 25	Acute Tox. 4 (H302)		01-2119480419-30-XXXX
Isobutane	200-857-2	75-28-5	5 - <10	Flam. Gas 1 (H220) Press. Gas		01-2119485395-27-XXXX
Dimethyl ether	204-065-8	115-10-6	5 - <10	Flam. Gas 1 (H220) Press. Gas		01-2119472128-37-XXXX
Propane	200-827-9	74-98-6	1 - <3	Flam. Gas 1 (H220) Press. Gas		01-2119486944-21-XXXX
2,2-dimethylpropan-1-ol, tribromo derivative	253-057-0	36483-57-5	1 - <3	Eye Irrit. 2 (H319)		01-2119935159-32-XXXX

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention.
Inhalation	Remove to fresh air. May cause allergic respiratory reaction. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Get immediate medical advice/attention.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists. Consult an ophthalmologist.
Skin contact	May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor. Wash off immediately with soap and plenty of water for at least 15 minutes.
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. May

Safety Data Sheet

BOSTIK FP404 FIRE RET PU GUNFOAM
Supersedes Date: 07-Sep-2018

Revision Date 04-Jun-2019
Revision Number 2

produce an allergic reaction. Get immediate medical advice/attention. Clean mouth with water. Drink 1 or 2 glasses of water.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. See section 8 for more information. Avoid breathing vapours or mists.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms May cause allergy or asthma symptoms or breathing difficulties if inhaled. Coughing and/or wheezing. Itching. Rashes. Hives. Burning sensation. Difficulty in breathing.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors May cause sensitisation in susceptible persons. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Dry chemical. Carbon dioxide (CO₂). Water spray.

Unsuitable extinguishing media DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated. Product is or contains a sensitiser. May cause sensitisation by inhalation and skin contact. May cause sensitisation by skin contact.

5.3. Advice for firefighters

Special protective equipment for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid breathing vapours or mists.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Safety Data Sheet

BOSTIK FP404 FIRE RET PU GUNFOAM
Supersedes Date: 07-Sep-2018

Revision Date 04-Jun-2019
Revision Number 2

Methods for containment Keep out of drains, sewers, ditches and waterways. Stop leak if you can do it without risk. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Flood with water to complete polymerization and scrape off floor.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid contact with skin and eyes. Avoid breathing vapours or mists. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Provide extract ventilation to points where emissions occur. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Take off contaminated clothing and wash it before reuse.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Remove and wash contaminated clothing and gloves, including the inside, before re-use.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals. Keep out of the reach of children. Store locked up.

7.3. Specific end use(s)

Specific Use(s)
Aerosol.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Exposure Limits

Safety Data Sheet

BOSTIK FP404 FIRE RET PU GUNFOAM
Supersedes Date: 07-Sep-2018

Revision Date 04-Jun-2019
Revision Number 2

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical name	European Union
Dimethyl ether 115-10-6	TWA: 1000 ppm TWA: 1920 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)	
Dimethyl ether (115-10-6)	
Type	Worker Long term Systemic health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	1894 mg/m ³

Derived No Effect Level (DNEL)	
Dimethyl ether (115-10-6)	
Type	Consumer Long term Systemic health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	471 mg/m ³

Predicted No Effect Concentration (PNEC) No information available.

Predicted No Effect Concentration (PNEC)	
Dimethyl ether (115-10-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.155 mg/l
Marine water	0.016 mg/l
Microorganisms in sewage treatment	160 mg/l
Freshwater sediment	0.681 mg/kg dry weight
Soil	0.45 mg/kg dry weight

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face protection Tight sealing safety goggles.
Skin and body protection Suitable protective clothing.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State Aerosol
Appearance No information available
Colour No information available
Odour Characteristic
Odour Threshold No information available

Property	Values	Remarks • Method
pH	No data available	
Melting point / freezing point	No data available	
Boiling point / boiling range	Not applicable, Aerosol	No data available
Flash Point	Not applicable, Aerosol	No data

Safety Data Sheet

BOSTIK FP404 FIRE RET PU GUNFOAM
Supersedes Date: 07-Sep-2018

Revision Date 04-Jun-2019
Revision Number 2

Evaporation Rate	available	
Flammability (solid, gas)	No data available	
Flammability Limit in Air	No data available	
Upper flammability or explosive limits	16	
Lower flammability or explosive limits	3	
Vapour Pressure	600	kPa @ 20 °C
Vapour Density	No data available	
Relative Density	No data available	
Water Solubility	Immiscible in water	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
Kinematic Viscosity	No data available	
Dynamic Viscosity	No data available	
Explosive properties	No data available	
Oxidising properties	No data available	

9.2. Other information

Solid content (%)	No information available	
Softening Point	No information available	
Molecular Weight	No information available	
VOC (volatile organic compound)	160.5 g/L / 15.3 %	European directive n°2010/75/UE
Density	1.049 g/cm ³	
Bulk Density	No information available	

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion Data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks. Excessive heat.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

Safety Data Sheet

BOSTIK FP404 FIRE RET PU GUNFOAM
Supersedes Date: 07-Sep-2018

Revision Date 04-Jun-2019
Revision Number 2

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product information

Inhalation	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Specific test data for the substance or mixture is not available. May cause sensitisation in susceptible persons. (based on components). May cause irritation of respiratory tract. Harmful by inhalation.
Eye contact	Irritating to eyes. Causes serious eye irritation.
Skin contact	Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). May cause sensitisation by skin contact. Causes skin irritation.
Ingestion	Specific test data for the substance or mixture is not available. May cause additional affects as listed under "Inhalation". Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea. Harmful if swallowed. (based on components).

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing. Coughing and/ or wheezing. Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes.
-----------------	--

Numerical measures of toxicity

Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	1,886.60 mg/kg
ATEmix (inhalation-dust/mist)	2.62 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Isocyanic acid, polymethylenepolyphenylene ester 9016-87-9	LD 50 > 10000 mg/kg (Rat)	LD 50 > 9400 mg/kg (Rabbit)	=1.5 mg/L (Rat) 4 h
2-Propanol, 1-chloro-, phosphate (3:1) 13674-84-5	LD50 > 500 - < 2000 mg/kg (male) LD50 = 632 mg/kg (female) [Rat]	LD50 > 2000 mg/kg (Rat) OECD 402	> 5.05 mg/L (Rat) 4 h
Isobutane 75-28-5			= 658 mg/L (Rat) 4 h
Dimethyl ether 115-10-6			= 164000 ppm (Rat) 4 h
Propane 74-98-6			> 800000 ppm (Rat) 15 min
2,2-dimethylpropan-1-ol, tribromo derivative 36483-57-5	= 1630 mg/kg (Rat)		

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Safety Data Sheet

BOSTIK FP404 FIRE RET PU GUNFOAM
Supersedes Date: 07-Sep-2018

Revision Date 04-Jun-2019
Revision Number 2

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Component Information					
Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit				Mild skin irritant

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitisation May cause sensitisation by inhalation. May cause sensitisation by skin contact.

Component Information			
Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig		No sensitisation responses were observed
OECD Test No. 429: Skin Sensitisation: Local Lymph Node Assay	Mouse		sensitising

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Chemical name	European Union
Isobutane 75-28-5	Muta. 1B

Carcinogenicity Classification based on data available for ingredients. Contains a known or suspected carcinogen.

Component Information		
Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)		
Method	Species	Results
OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies	Rat	Carcinogenic

Chemical name	European Union
Isobutane 75-28-5	Carc. 1A

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause respiratory irritation.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor

Safety Data Sheet

BOSTIK FP404 FIRE RET PU GUNFOAM
Supersedes Date: 07-Sep-2018

Revision Date 04-Jun-2019
Revision Number 2

	plants		Micro-organisms		
Isocyanic acid, polymethylenepolyphenylene ester 9016-87-9	ErC50 (72h) >1640 mg/L Algae (scenedesmus subspicatus) (OECD 201)	CL50 (96h) >1000 mg/L Fish (Danio rerio)	-	EC50 (24H) >1000 mg/L Daphnia magna	-
2-Propanol, 1-chloro-, phosphate (3:1) 13674-84-5	EC50 (72 h) = 82 mg/L (Pseudokirchneriella subcapitata) OECD 201	LC50 (96 h) = 51 mg/L (Pimephales promelas)	-	EC50 (48 h) = 131 mg/L (Daphnia magna)	-

12.2. Persistence and degradability

Persistence and degradability No information available.

Component Information			
Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)			
Method	Exposure time	Value	Results
OECD Test No. 302C: Inherent Biodegradability: Modified MITI Test (II)	28 days	0% biodegradation	Not readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulative potential There is no data for this product.

Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Isocyanic acid, polymethylenepolyphenylene ester 9016-87-9	-	200
2-Propanol, 1-chloro-, phosphate (3:1) 13674-84-5	2.68	4.6
Isobutane 75-28-5	2.88	1.97
Dimethyl ether 115-10-6	-0.18	-
Propane 74-98-6	2.3	-

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment This preparation contains no substance considered to be persistent, bio-accumulating nor toxic (PBT).

Chemical name	PBT and vPvB assessment
2-Propanol, 1-chloro-, phosphate (3:1) 13674-84-5	The substance is not PBT / vPvB
Isobutane 75-28-5	The substance is not PBT / vPvB
Dimethyl ether 115-10-6	The substance is not PBT / vPvB
Propane 74-98-6	The substance is not PBT / vPvB
2,2-dimethylpropan-1-ol, tribromo derivative	The substance is not PBT / vPvB

Safety Data Sheet

BOSTIK FP404 FIRE RET PU GUNFOAM
Supersedes Date: 07-Sep-2018

Revision Date 04-Jun-2019
Revision Number 2

36483-57-5

12.6. Other adverse effects

Other Adverse Effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

Waste codes / waste designations according to EWC / AVV 16 05 05 gases in pressure containers other than those mentioned in 16 05 04. Waste codes should be assigned by the user based on the application for which the product was used.

Other information Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN Number UN1950
14.2 Proper Shipping Name Aerosols
14.3 Transport hazard class(es) 2
Labels 2.2
14.4 Packing Group Not regulated
Description UN1950, Aerosols, 2, (E)
14.5 Environmental hazards Not applicable
14.6 Special Provisions 327, 625, 344, 190
Classification Code 5A
Tunnel restriction code (E)
Limited Quantity (LQ) 1 L

IMDG

14.1 UN Number UN1950
14.2 Proper Shipping Name Aerosols
14.3 Transport hazard class(es) 2.1
14.4 Packing Group Not regulated
Description UN1950, Aerosols, 2.1
14.5 Marine Pollutant Np
14.6 Special Provisions 63,190, 277, 327, 344, 381, 959
Limited Quantity (LQ) See SP277
EmS-No. F-D, S-U
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information available

Air transport (ICAO-TI / IATA-DGR)

14.1 UN Number UN1950
14.2 Proper Shipping Name Aerosols, flammable
14.3 Transport hazard class(es) 2.1
14.4 Packing Group Not regulated
Description UN1950, Aerosols, flammable, 2.1
14.5 Environmental hazards Not applicable
14.6 Special Provisions A145, A167, A802

Safety Data Sheet

BOSTIK FP404 FIRE RET PU GUNFOAM
Supersedes Date: 07-Sep-2018

Revision Date 04-Jun-2019
Revision Number 2

Limited Quantity (LQ)	30 kg G
ERG Code	10L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P3a - FLAMMABLE AEROSOLS

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National Regulations

France

Occupational Illnesses (R-463-3, France)

Chemical name	French RG number
Isocyanic acid, polymethylenepolyphenylene ester 9016-87-9	RG 62

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV

Flammable liquid (R10), EEC: refer to Annex III No. 1 (fire and explosion hazards) and § 7 paragraph 3

Safety Data Sheet

BOSTIK FP404 FIRE RET PU GUNFOAM
Supersedes Date: 07-Sep-2018

Revision Date 04-Jun-2019
Revision Number 2

Water hazard class (WGK) WGK 1

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Not Listed

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H220 - Extremely flammable gas
H302 - Harmful if swallowed
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335 - May cause respiratory irritation
H351 - Suspected of causing cancer
H373 - May cause damage to organs through prolonged or repeated exposure

Legend

SVHC: Substances of Very High Concern for Authorisation:

Legend SECTION 8: Exposure controls/personal protection
TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)
Ceiling Maximum limit value * Skin designation
PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
STOT RE Specific target organ toxicity - Repeated exposure
STOT SE Specific target organ toxicity - Single exposure
EWC: European Waste Catalogue

Key literature references and sources for data

Classification and labeling data calculated from data received from raw material suppliers

Prepared By Product Safety & Regulatory Affairs

Revision Date 04-Jun-2019

Indication of changes

Revision note SDS sections updated, 2, 3, 4, 5, 6, 7, 8, 10, 11, 12, 13, 15.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of

Safety Data Sheet

BOSTIK FP404 FIRE RET PU GUNFOAM
Supersedes Date: 07-Sep-2018

Revision Date 04-Jun-2019
Revision Number 2

its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet