

MIXING / PRIMING INSTRUCTIONS



ENVIRO-SLIDE READY-TO-USE SPATTER COAT AND FORM RELEASE

ENVIRO-SLIDE is our premium concrete repellent coating to prevent concrete from adhering to ready mix trucks and concrete pumping equipment. ENVIRO-SLIDE facilitates easy removal of dried concrete from forms. Apply with a single thin coat. It is non-staining, reduces waste and increases productivity.

Remember: The information contained herein is, to the best of our knowledge and belief, accurate. However, since handling conditions and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. Concrete Pump Supply LLC's responsibility for any claim arising out of breach of warranty, negligence, and strict liability or otherwise is limited to the purchase price of the materials.

CreteBuster provides lubrication for pipe and hose. The responsibility to provide a safe workplace remains with the user. Each user should consider the health hazards and safety information contained herein as a guide and should take any pre-caution necessary to ensure a safe work environment.

More water and primer may be needed in cases where the hopper is extraordinarily large or the intake valve is placed high up on the hopper. In all cases, primer should be completely charged into system ahead of ready-mix. In all cases, primer should be completely charged into system ahead of ready-mix.

Horizontal pumping jobs may require more priming agent. A sponge may be placed ahead of the mixture to insure that system interior is completely coated.

5300 Riverview RD. SE
Mableton, GA 30126 USA
678.370.0000
877.434.7867
www.concretepumpsupply.com

