

# I. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER

Product Name:	Gold Topaz	
General Use:	Adhesives	
<b>Product Description:</b>	Low Humidity Eyelash Adhesive	
Company Name:	Sinful Lashes	
Address:	15617-A Ventura Blvd. Encino, CA 91436	
Phone:	(818) 508-6544	
Web Address:	www.sinfullashes.com/	

### II. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	wt%	CAS Registry No.
Ethyl Cyano Acrylate	95%	7085-85-0
PMMA	4.5%	9065-11-6
Carbon black	0.5%	1333-86-4

#### III. HAZARDS IDENTIFICATION

**Emergency Overview:** Vapor is irritating to eyes, skin and mucous membranes and respiratory tract.

Potential Health Effects: May cause sensitization by inhalation. Narcotic effects, Headache, dizziness,

vomiting. Skin: Dryness. Eye: Irritation.

Potential Environmental Effects: Not Available.

Signs of Symptoms and Exposure: Vapor is irritating to eyes and mucous membranes above TLV.

Prolonged and repeated overexposure to vapors may produce symptoms of non-allergic asthma in sensitive individuals

**Existing Conditions Aggravated by Exposure:** Unknown

Target Organ and Other Health Effects: \*Literature referenced

Ingredients.

Ethylcyanoacrylate ALG IRR RES

Carcinogen NTP IARC IRR RES

N/A Not Aplicable IRR Irritant, ALG Allergen, RES Respiratory

# **IV. FIRST AID MEASURES**

DESCRIPTION OF NECESSARY MEASURES, SUBDIVIDED ACCORDING TO THE DIFFERENT ROUTES OF EXPOSURE, IE, INHALATION, SKIN AND EYE CONTACT, AND INGESTION

### If on skin:

Remove contaminated clothing/shoes and wipe off excess from skin. Wash exposed area with soap and water.

#### If inhaled:

Don't breath gas/fumes/vapor/spray

(appropriate wording to be specified by the manufacture). (S23)



Evacuate from further exposure. If unconsciousness occurs, seek immediate medical assistance and call a physician.

If breathing difficulty occurs, have oxygen inhalation.

### If in eyes:

Immediately flush eyes with running water for at least 15 minutes. If redness, itching or a burning sensation develops, see a physician.

# If ilngested:

Ingestion is not likely. See supplemental page for emergency procedures.

### V. FIREFIGHTING MEASURES

### Flash Point:

Above 95°C. Method: Cleveland open cup. (Recommended)

### **Extinguishing Agents:**

Carbon Dioxide, form, dry chemical

**Unusual Fire or Explosion Hazards:** 

None

### VI. ACCIDENTAL RELEASE MEASURES

**Evacuate None Essential Personal.** 

Shut Off All Sources Of Ignition; No Fires, Smoking or Flames in Area.

Ventilate Area After Pick Up is Complete.

### Smal Spills:

Absorb with inert material such as a dry cloth or sand. Scoop up and place in containers for proper disposal. Keep spills and cleaning runoff out of the municipal sewers and open bodies of water. Decontaminate all clothing and the spill area with detergent and large amounts of water.

# Large Spills:

Dike for later disposal. Wash with plenty of water

#### VII.HANDLING AND STORAGE

# Handling Precautions:

Keep away from sources of ignition and heat. No smoking of flames in working area. Take precautionary measures against static discharges. Avoid skin or eye contact. (S24/25) Wear proper protective equipment. Avoid prolonged or repeated breathing of vapors and mists. Do not take internally. Use only in a well ventilated area to keep air concentration below exposure limit. Instal emergency showers and eye wash facility in working area. Keep container tightly closed when not in use. Keep out of reach of children. (S2)

# Storage Requirements:

Keep container tightly closed when not in use. Keep away from all possible sources of ignition. Store in a cool, dry, well ventilated location. Keep away from combustable materials, heat, steam pipe or sunlight. Keep away from oxidizing materials. Containers, even those that have been emptied, will retain products residue vapors and are subject to proper waste disposal, as above.



### Other Precautions:

Wash hands, face and gargle after work. Practice good personal hygiene after using this material, especially before eating, drinking, smoking or using the rest room.

## VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Respiratory Protection (Specify Type):

Chemical cartridge respirator with organic vapor ventilation local exhausts. Should be used control vapors in work area. Mechanical (General) should use a breathing mask.

Protective Gloves:

(Polyethylene gloves, No rubber.

**Eye Protection:** 

Safety glasses, face shield.

**Skin Protection:** 

Other protective clothing or equipment impervious clothing, apron and boots. Barrier creams, etc.

# IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE : BLACK LIQUID ODOR : SHARP, IRRITATING.

PH: N/A

WATER SOLUBILITY: INSOLUBLE (POLYMERIZED BY WATER)

BOILING POINT: ABOVE 190 °C (374 °F)

**MELTING POINT: N/A** 

SPECIFIED GRAVITY (H2O =1): 09 ~ 1.1

VAPOR PRESSURE (AT25 °C): 1PA

VAPOR DENSITY (AIR=1): 4.9

EVAPORATION RATE (BUTYL ACETATE =1): N/A

# X. STABILITY AND REACTIVITY

### Conditions to Avoid:

High humidity, high temperature or direct sunlight.

Stability:

Stable (Cool and dry area.).

Materials to Avoid:

Polymerized by contact with water, alcohols, amines, alkalies.

Hazardous Decomposition or Byproducts:

CO2, Oxides and nitrogen and unknown hydrocarbons.

### XI. TOXICOLOGICAL INFORMATION

### **Toxicity:**

Skin contact may cause burns. Bond skin rapidly and strongly. Skin and eye irritant.



Routes of entry:

Inhalation (Yes), Skin (Yes), Ingestion (Yes).

Literature Referenced Carcinogen

# XII. ECOLOGICAL INFORMATION

NO DATA AVILABLE

### XIII. DISPOSAL CONSIDERATION

# Waste Disposal Method:

Don't pour down drain. Follow domestic and local environmental regulations. Precautions to be taken in handling and storing: Avoid unnecessary exposure to air and moisture. Don't store above 25 °C and in direct sunlight. Keep container lids tightly closed.

## Other Precautions:

Avoid contact with skin and eyes. Protect eyes, skin and clothing from contact with liquid product. Wear recommended equipment.

### XIV. TRANSPORT INFORMATION

# U.S. DEPARTMENT OF TRANSPORTATION GROUND TRANSPORT (49 CFR 172)

# **Proper Shipping Name:**

Unrestricted (Not more than 450 liters.) Combustable liquids N. O. S. (Cyanoacrylate ester) (More than 450 liters)

### Hazard Class or Division:

Unrestricted (Not more than 450 liters.) Combustable liquids. (More than 450 liters)

### **Identification Number:**

None (Not more than 450 liters.) NA1993 (More than 450 liters)

# Marine pollutant:

None.

# INTERNATIONAL AIR TRANSPORTATION (ICA/IATA)

# **Proper Shipping Name:**

Unrestricted

# Class or division:

Unrestricted

### **UN or ID Number:**

None

### WATER TRANSPORTATION (IMO/IMDG)

## **Proper Shipping Name:**

Unrestricted



Hazard Class or Division:

None

**Identification Number:** 

None



Marine Pollutant:

None

# XV. REGULATORY INFORMATION

# CA Proposition 65:

No California Proposition 65 chemicals are known to be present.

# TSCA 9(b) Inventory Status:

All components are listed or are exempt from listing on Toxic Substances Control Act Inventory.

EINECS All components are listed on EINECS

### XVI. OTHER INFORMATION

ESTIMATED NFPA(R) CODE:

**HEALTH HAZARD: 2** 

FIRE HAZARD: 2

**REACTIVITY HAZARD: 1** 

SPECIFIC HAZARD: DOES NOT APPLY

ESTIMATED HMIS(R) CODE:

**HEALTH HAZARD: 2** 

FLAMMABILITY HAZARD: 2

NFPA IS A REGISTERED TRADEMARK OF THE FIRE PROTECTION ASSN.

# HMIS IS A REGISTERED TRADEMARK OF THE NATIONAL PAINT AND COATING ASSN.

To the best of knowledge, the information contained herein is accurate. However, neither our company nor any subsidiaries assume any liability whatsoever for the accuracy or completeness of the information contained herein. All materials may present unknown.