



# 65TiiCO25

## **Tile Insert Drain**

Full stainless steel drainage unit with centre outlet.

The 65Ti25 is a Tile Insert Drain manufactured from 1.5mm thick 316 marine grade stainless steel.

Suitable for tiles up to 10mm thick.

Refer to AS3500 for outlet pipe sizes specific to your installation.

### **SPECIFICATIONS + DIMENSIONS**

Channel Width 72mm Channel Depth 27mm

**Length(s)** 900mm 1000mm 1200mm


Outlet Size DN50



Code 65TiiCO25
Range 65
Grate Style Ti


Category Fixed-Length Units

**Channel Material** Stainless Steel **Steel Grade** 316



Grates longer than 1500mm supplied in sections. Tile Inserts longer than 1200mm supplied in sections. Channels over 3000mm supplied in sections with joiner. +/-2mm tolerance on dimensions.

### STORMTECH COLOUR FINISHES



Electroplate finishes subject to natural variation with time and local environment. Factors such as pools/surf beaches may require electropolishing. Contact us for suitability.

#### PRODUCT APPLICATIONS

Bathroom Drainage Aged / Health Care Drainage Balcony Drainage Commercial Drainage Pool and Spa Area Drainage Hospitality Drainage Shower Drainage Multi-Residential Drainage Special Needs Drainage Threshold Drainage Suspended Slab Drainage Wet Area Drainage

Copyright © Stormtech Pty Ltd. Patent 733361. Drawings not to scale, please use dimensions shown. Downloaded 16/06/2022 (please check for updates)





