


# Protects against termites, ants and other destructive insects



of Mould resistant

Versatile Sanitary Grade Construction Silicone Sealant

Colour - Light Grev



- 𝞯 Termite-Proof Silicone for Joining Ant Caps
- 𝞯 Pesticide free
- 𝞯 Inhibits mould and mildew growth
- Adheres to most building materials including plastics
- 𝞯 Neutral cure
- Withstands movement to ±25%
- 𝞯 Working temperature -20° C to +100° C

www.novithor.com

300 g

## **NOVITHOR**<sup>™</sup> TERMITE PROOF FLEXI-GEL

### APPLICATIONS:

Specifically designed for use with:

 Termite resistant materials
Aluminium, zincalume, galvanised metal, PVC,

concrete and stainless steel Meets the requirements of

AS 3660 Termite management.

#### DIRECTIONS:

- 1. Surface must be completely clean and dry.
- 2. Extrude and tool sealant fully into joint.
- Extrude ample sealant onto ant capping to ensure continuous seal, overlap ant caps by 40 mm. Hold in position with weights till sealant cures.
- Sealant should skin within 10 minutes and cure at a rate of 1-2 mm in 24 hours.
- 5. Use Mineral Turpentine to remove uncured sealant.



#### Precautions for Use:

Do not apply sealant to wet surfaces. Sealant cannot be painted over.

Use of eye protection is always recommended. Direct contact with uncured product and vapours may irritate eyes, throat, nasal membranes and skin. Wear suitable protective clothing and gloves.


Safety & First Aid: Sealant will release methylethylketoxime vapour until fully cured. Avoid breathing vapours.

Use in well ventilated conditions. If product is introduced into eyes, immediately flush with water for 15 minutes.

If poisoning occurs, contact a doctor or Poisons Information Centre. Phone 13 11 26.

#### Shelf Life:

18 months from date of manufacture when stored in cool, dry conditions, below 25 °C. Refer to product Data Sheet or SDS for further technical or safety information.



#### ENSYSTEX AUSTRALASIA PTY LTD ABN 53 102 221 965

Unit 3, The Junction Estat 4-6 Junction Street AUBURN NSW 2144



