

## // 155AA

**Compressed air 20 bar (300 psi) - Heavy duty**

**Tube:** black SBR/NBR - oil mist resistant.

**Reinforcement:** high tensile textile cords.

**Cover:** black SBR - abrasion and ozone resistant.

**Application:** compressed air designed for heavy duty applications.

**Constant operation:** -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↻		↻		∩		%		Ⓜ	
mm	in	mm	in	bar	psi	bar	psi	mm	in			kg/m	lb/ft
19,0	3/4"	29,00	1,14	20	300	60	900					0,550	0,37
22,0	7/8"	32,00	1,26	20	300	60	900					0,620	0,42
25,0	1"	35,00	1,38	20	300	60	900					0,690	0,47
28,0	1 1/8"	38,00	1,50	20	300	60	900					0,790	0,54
30,0	1 3/16"	42,00	1,65	20	300	60	900					0,840	0,57
32,0	1 1/4"	44,00	1,73	20	300	60	900					0,880	0,60
35,0	1 3/8"	47,00	1,85	20	300	60	900					0,950	0,64
38,0	1 1/2"	50,00	1,97	20	300	60	900					1,030	0,70
40,0	1 9/16"	52,00	2,05	20	300	60	900					1,070	0,72
45,0	1 3/4"	57,00	2,24	20	300	60	900					1,200	0,81
48,0	1 7/8"	60,00	2,36	20	300	60	900					1,270	0,86
51,0	2"	63,00	2,48	20	300	60	900					1,330	0,90
51,0	2"	65,00	2,56	20	300	60	900					1,650	1,11
55,0	2 1/6"	69,00	2,72	20	300	50	730					1,760	1,19
60,0	2 3/8"	76,00	2,99	20	300	50	730					2,200	1,48
63,0	2 1/2"	79,00	3,11	20	300	50	730					2,290	1,54
76,0	3"	92,00	3,62	20	300	50	730					2,800	1,89
90,0	3 1/2"	106,00	4,17	20	300	50	730					3,240	2,18
102,0	4"	118,00	4,65	20	300	50	730					3,660	2,46
152,0	6"	170,00	6,69	20	300	50	730					6,220	4,19

