



Soft PVC hose with knitted textile reinforcement for water delivery in flower-growing and agriculture.



SMOOTH SURFACES



FLEXIBILITY



ABRASION RESISTANCE



TEMPERATURE RANGE

-5°C +65°C
23°F +140°F



CHEMICAL RESISTANCE

PVC table



CRUSHING RESISTANCE

Ø I.D.	Ø I.D.	Ø O.D.	TOTAL THICKNESS	WEIGHT	BENDING RADIUS	WORKING PRESSURE 1:3 23°C	BURSTING PRESSURE 23°C	COIL LENGTH	AVAILABILITY
inch	mm	mm	mm	g/m	mm	bar	bar	m	
	12	16	2	115	190	10	30	25/50	IN STOCK
1/2	13	18.5	2.75	170	175	10	30	25/50	IN STOCK
	15	19	2	140	220	10	30	25/50	IN STOCK
5/8	16	22	3	235	207	10	30	25/50	IN STOCK
3/4	19	24.5	3	250	280	8	24	25/50	IN STOCK
3/4	19	26	3.5	310	250	8	24	25/50	IN STOCK
1	25	32	3.5	390	330	8	24	25/50	IN STOCK
1	25	32.5	3.75	410	315	8	24	25/50	IN STOCK

All technical specifications apply to a temperature of 23°C ± 2°C (ISO 291). - Tolerance on all specifications ± 5%.