

// 185AH

**Compressed air 20 bar (300 psi) - Standard duty****Tube:** black synthetic elastomer - oil mist resistant.**Reinforcement:** high tensile textile cords.**Cover:** red synthetic elastomer - abrasion and ozone resistant.**Application:** compressed air and general industrial applications.**Constant operation:** -10 °C +60 °C (+14 °F +140 °F)

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
6,0	1/4"	12,00	0,47	20	300	60	900	48,0	1,89		0,120	0,09	
8,0	5/16"	14,00	0,55	20	300	60	900	64,0	2,52		0,145	0,10	
10,0	3/8"	17,00	0,67	20	300	60	900	80,0	3,15		0,205	0,14	
13,0	1/2"	21,00	0,83	20	300	60	900	104,0	4,09		0,280	0,19	
19,0	3/4"	28,00	1,10	20	300	60	900	152,0	5,98		0,460	0,31	
25,0	1"	35,00	1,38	20	300	60	900	200,0	7,87		0,645	0,44	

// 185AK

**Compressed air 20 bar (300 psi) - Standard duty****Tube:** black synthetic elastomer - oil mist resistant.**Reinforcement:** high tensile textile cords.**Cover:** yellow synthetic elastomer - abrasion and ozone resistant.**Application:** compressed air and general industrial applications.**Constant operation:** -10 °C +60 °C (+14 °F +140 °F)

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
13,0	1/2"	21,00	0,83	20	300	60	900	104,0	4,09		0,325	0,22	
19,0	3/4"	28,00	1,10	20	300	60	900	152,0	5,98		0,460	0,31	
25,0	1"	35,00	1,38	20	300	60	900	200,0	7,87		0,645	0,44	

// 186AA

**Compressed air 20 bar (300 psi) - Heavy duty****Tube:** black synthetic elastomer - oil mist resistant.**Reinforcement:** high tensile textile cords.**Cover:** black synthetic elastomer - abrasion and ozone resistant.**Application:** compressed air and general industrial applications.**Constant operation:** -10 °C +60 °C (+14 °F +140 °F)

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
6,0	1/4"	14,00	0,55	20	300	60	900	48,0	1,89		0,185	0,13	
8,0	5/16"	17,00	0,67	20	300	60	900	64,0	2,52		0,255	0,18	
10,0	3/8"	19,00	0,75	20	300	60	900	80,0	3,15		0,300	0,21	
13,0	1/2"	23,00	0,91	20	300	60	900	104,0	4,09		0,415	0,28	
19,0	3/4"	30,00	1,18	20	300	60	900	152,0	5,98		0,575	0,39	
25,0	1"	37,00	1,46	20	300	60	900	200,0	7,87		0,775	0,53	