









## JAMAICA S/L

915119



Flexible layflat PVC hose, with polyester yarn reinforcement, resistant to elongation, for pressurized delivery of liquids in general.

### DETAILS

	SMOOTH SURFACE	*****
	FLEXIBILITY	*
	ABRASION RESISTANCE	***
	TEMPERATURE RANGE	-5 °C 60 °C
	CHEMICAL RESISTANCE	PVC Table
	CRUSHING RESISTANCE	*

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23 °C bar	working press. at 40 °C bar	bursting press. at 23 °C bar	total thickness mm	weight meter g/m	# wires for angle n° x a°	working resistance kg	tensile breaking load kg	coil length m	Availability
63	2 1/2	63.5	66	4	2.4	12	1.3	370	48X75°	228	530	50/100	On demand
76	3	76	79	4	2.4	12	1.5	475	60X75°	268	625	50/100	On demand
80		80	83	4	2.4	12	1.5	490	60X75°	280	655	50/100	On demand
102	4	102	105	3	2	12	1.5	650	72X78°	356	830	50/100	On demand
152	6	152	156.5	3	1.8	9	2.3	1250	72X78°	534	1250	50/100	On demand
204	8	204	208.5	2.5	1.5	8	2.3	1700	120X80°	710	1700	50	On demand

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

The tolerance on all specifications ±5% (Tolerance Percentage is applicable on ALL DATA across our range)