

// 195AT



Compressed air 20 bar (300 psi) - Polyurethane - Pneumatic tools

Tube: black polyurethane/PVC - oil mist resistant.

Reinforcement: high tensile textile cords.

Cover: light blue synthetic elastomer - abrasion and ozone resistant.

Application: compressed air. Specially designed for pneumatic tools and paint spray.

Constant operation: -20 °C +60 °C (-4 °F +140 °F)

↔		↔		↻		↻		⌒		⌒		
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
6,0	1/4"	10,00	0,39	20	300	60	900	24,0	0,94		0,065	0,05
8,0	5/16"	12,00	0,47	20	300	60	900	32,0	1,26		0,080	0,06
10,0	3/8"	15,00	0,59	20	300	60	900	40,0	1,57		0,115	0,08
13,0	1/2"	19,00	0,75	20	300	60	900	52,0	2,05		0,185	0,13
16,0	5/8"	23,00	0,91	20	300	60	900	64,0	2,52		0,260	0,18
19,0	3/4"	26,00	1,02	20	300	60	900	76,0	2,99		0,305	0,21
25,0	1"	33,00	1,30	20	300	60	900	100,0	3,94		0,450	0,31

// 191AK



Compressed air 20 bar (300 psi) - PVC exceeds AS/NZS 2554/B

Tube: black PVC - oil mist resistant.

Reinforcement: high tensile textile cords.

Cover: yellow ribbed PVC with longitudinal blue stripes - abrasion and ozone resistant.

Application: compressed air and general industrial applications. Also suitable for crop spraying of fertilizers, pesticides and weed killers.

Constant operation: -5 °C +60 °C (+23 °F +140 °F)

↔		↔		↻		↻		⌒		⌒		
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
10,0	3/8"	16,00	0,63	20	300	64	960	80,0	3,15		0,170	0,12
13,0	1/2"	19,00	0,75	20	300	64	960	104,0	4,09		0,205	0,14
19,0	3/4"	27,00	1,06	20	300	64	960	152,0	5,98		0,370	0,25
25,0	1"	34,00	1,34	20	300	64	960	200,0	7,87		0,525	0,36