


Floor Lamp | 220-240 V 1 topLED 20 W DC - 25 W AC | CRI 90 8545



Technical data	
Construction year	2018
Туре	Floor Lamp
Installation position	Floor
Installation environment	Indoor
Light Source	LED
Optics	General Lighting
Light emission direction	downward
Power	20 W
Source lumens	2534 lm
Frequency	60 - 50 Hz
CCT / Tone	3000 K
Colour rendering index	90 Ra
C.C. / C.V.	AC
Safety class	2
IP	IP20
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	PUSH DIM
Directional	Swivelling
total angle (vertical plane)	0°
total angle (horizontal plane)	360 °
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	4 m
Electric socket	Type F+E
Resin potting	No
Type of light emission	Single emission
Net weight	6.13 Kg
Electrostatic discharge protection	No
Surge protection	No





Finishing casing		
Material	Aluminium	
Colour	Embossed white RAL 9003	
Processing	Coating	

Finishing diffuser		
Material	PC	
Colour	opaline	
Processing	Satin finishing	

Finishing mounting frame		
Material	steel	
Colour	Embossed white RAL 9003	
Processing	Coating	



## Floor Lamp | 220-240 V | 1 top LED 20 W DC - 25 W AC | CRI 90 | Base $\bf 8545$


Single emission floor lamp for indoor application. The warm white LED light source with a general lighting light distribution is composed of 1 topled LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 2534 lm, with a 126.7 lm/W nominal luminous efficacy.


The device body is made of aluminium and features a embossed white ral 9003 finish, processed by means of coating; the diffuser is made of PC with a satin finishing treatment; the mounting frame is made of steel, with a embossed white ral 9003 finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 6.13 kg.

The total absorbed power is 25 W. The power supply cable is included and features a 4 m lenght.

The device features protection class II and can be floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.





## Energy efficiency class

This product contains a light source of energy efficiency class E.

Illuminotechnical Features	
Light Output Ratio (LOR)	52 %
Source lumens	2534 lm
Delivered lumens	1324 lm
Consumption	25 W
Luminaire efficacy	52 lm/W
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Junction temperature (lighting fixture)	80
Standard Operating Ambient Temperature	25
LED Life / Failure Ratio	
L80 B20 C0 80h	

UGR	
UGR axial	32.9
UGR transversal	32.4
X=4H   Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Light distribution simmetry	Symmetrical
C0/C180 optics	112°