

Product Family: Marchesa

Sku Tested: S8517

Related Models N/A

Test Voltage: 120 OR 227V

Control Type: ELV, TRIAC, MLV

Test Notes: Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

Manufacturer	Product	Model Number	Test Voltage (V)	Measured Dimming Range	Comments
				Low End	
Adaptive Phase Dimmers					
Control4	Adaptive	C4-APD120	120	0.3%	
Legrand	Adorne Touch (ELV)	ADTH700RMTUM1	120	43.0%	Flicker below 43%; Turn on time >0.5s at the lowest dimming level
Legrand	Adorne Touch (TRIAC)	ADTH700RMTUM1	120	31.0%	Not Recommended
Legrand	Radiant	RH703PTUW	120	13.0%	
Legrand	Adorne (ELV)	ADTP703TUW4	120	9.0%	
Legrand	Adorne (TRIAC)	ADTP703TUW4	120	3.0%	Not Recommended
Cooper	AL Series	AAL06	120	0.9%	Turn on time >0.5s at the lowest dimming level
Control4	Adaptive	C4-APD277	277	2.0%	
Reverse Phase Dimmers (ELV)					
Lutron	Nova T	NTELV-600	120	5.0%	
Lutron	Diva	DVELV-300P	120	3.0%	
Lutron	Maestro	MAELV-600	120	0.9%	Turn on time >0.5s at the lowest dimming level
Lutron	Skylark	SELV-300P	120	3.0%	
Leviton	Illumatech	IPE04-1LZ	120	4.0%	
Lutron	Maestro	RRD-6NA	120	0.8%	Turn on time >0.5s at the lowest dimming level
Leviton	SureSlide	6615-POW	120	13.0%	
Leviton	Decora	DSE06-10Z	120	2.0%	
Lutron	Caseta	PD-5NE	120	4.0%	
Lutron	Homeworks	HRD-5NE	120	N/A	Flashing at all dimming levels
Lutron	Homeworks	HQRD-6NA	120	0.6%	
Leviton	Renoir II	AWSMT-EBW	120	0.7%	
Lutron	Grafik-Eye	GRX-3103-A-G	120	0.6%	Turn on time >0.5s at the lowest dimming level
Leviton	Renoir II	AWSMT-EBW	277	1.0%	
Lutron	Grafik-Eye	GRX-3103-A-G	277	8.0%	Turn on time >0.5s at the lowest dimming level
Forward Phase Dimmers (TRIAC)					
Lutron	Maestro	MACL-153M-WH	120	2.0%	
Lutron	Diva	DVCL-153P	120	0.6%	
Legrand	Adorne Paddle	ADPD453LW2	120	13.0%	
Lutron	Ariadni	AYCL-153PH	120	1.0%	

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Schonbek's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Schonbek, and therefore Schonbek cannot ensure future compatibility. For any questions on this report, please contact Schonbek Customer Service at

+1 800 836 1892 or lighting.na@schonbek.com

Forward Phase Dimmers (TRIAC) Cont.					
Lutron	Skylark	SCL-153P-WH	120	0.4%	
Lutron	Maestro	MA-600-WH	120	20.0%	Flicker below 20%
Leviton	SureSlide	6674-POW	120	2.0%	
Lutron	Caseta	PD-6WCL	120	0.2%	
Legrand	Harmony	HCL453PW	120	0.9%	Flicker below 0.9%; Turn on time >0.5s at the lowest dimming level
Legrand	Radiant	RHCL453PW	120	4.0%	Flicker below 4%; Turn on time >0.5s at the lowest dimming level

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Schonbek's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Schonbek, and therefore Schonbek cannot ensure future compatibility. For any questions on this report, please contact Schonbek Customer Service at +1 800 836 1892 or lighting.na@schonbek.com