

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

1" LEDme

Round Adjustable Downlight (Remote Driver)

| Model | Color Temp & CRI | Lumens | CBCP | Finish |
|------------|------------------|--------|------|---|
| HR-LED232R | 27 2700K - 85 | 245 | 505 | BN Brushed Nickel GM Gun Metal WT White |
| | 30 3000K - 85 | 250 | 515 | |
| | 35 3500K - 85 | 265 | 546 | |
| | 40 4000K - 85 | 280 | 580 | |

Example: **HR-LED232R-27-BN**

DESCRIPTION

Perfect for ceilings, under cabinet and wall niches. LED Miniature Recessed Downlights offer a super low profile and Die-cast aluminum trim with a 25° cutoff angle for comfortable general and task lighting.

FEATURES

- Round recessed trim with interior open reflector for use with a remote driver
- Driver Required: LD-700MA03-EDIM-IS or LD-700MA09-EDIM-IS
- 5 year warranty

SPECIFICATIONS

| | |
|---------------------------|---|
| Construction: | Die-cast aluminum trim, aluminum heat sink and 20 gauge steel housing painted black. |
| Power: | 3W |
| Dimming: | ELV: 100-10% |
| Light Source: | Integrated LED 3 Step Mac Adam Ellipse |
| Rated Life: | 80000 Hours |
| Mounting: | Heavy gauge retention clips secures housing firmly to ceiling |
| Cut Out: | 2 1/2" |
| Finish: | Electrostatically Powder Coated:White, Electrostatically Powder Coated::Brushed Nickel, Electrostatically Powder Coated:::Gun Metal |
| Ceiling Thickness: | 1/2" - 1" |
| Operating Temp: | -4°F to 104°F (-20°C to 40°C) |
| Standards: | UL, cUL, Damp Location Listed, Non IC |



FINISHES:



LINE DRAWING:

